

# 231 LANKOFUGE SURFACE

NS5Plus

## WATERPROOFING AND SURFACE PROTECTION

### DESCRIPTION

A ready-to-use solvent-based product containing polysiloxane. It spreads by capillary action and establishes a stronghold within the substrate.

### BENEFITS

- Protection of façades or sloping surfaces.
- Does not alter surface appearance.
- Slight sheen effect.
- Excellent penetration.
- Can be used on damp substrates.
- Good resistance to weathering (UV rays, rain).

### INSTRUCTIONS

#### Preparation of substrates:

- The substrate must be clean, sound, dry or slightly damp. (After rain, wait at least 24 hours. After high pressure washing, wait at least 3 days).
- Efflorescence must be removed, and any cracks filled.
- Concrete, mortars and coatings must be at least 28 days old prior to application of 231 LANKOFUGE SURFACE.

### APPLICATION

- Apply by brush, soaking or spraying. For spraying, the nozzle must be held very close to the surface in order to ensure product penetration.
- 2 saturated coats must be applied. The second coat must be applied once the first coat has lost its sheen.
- Clean tools and accidental splashes immediately with white spirit.

### PRECAUTIONS

- Normal precautions for solvents (gloves, eye protection, ventilation).
- Respect the quantity recommendations with great care.
- Store 231 LANKOFUGE SURFACE below 35°C in its original, sealed packaging.
- Protect door frames and windows from accidental splashes.
- Cleans splashes immediately with white spirit.
- Consult safety datasheet.

### CONSUMPTION

These consumption rates are given as a guidance only and may vary subject to substrate condition.

- Concrete: 0.25 to 0.50 litres/m<sup>2</sup>.
- Coating: 0.50 to 0.80 litres/m<sup>2</sup>.
- Cellular concrete: 0.50 to 1.00 litres/m<sup>2</sup>.

### FIELD OF APPLICATION

Protection of façades or sloping surfaces made of:

- General concrete.
- Cellular concretes.
- Hydraulic coatings.
- Fibrous cement.
- Sandstone.
- Bricks and roofing tiles.
- Natural stonework.

It is recommended that a test is carried out beforehand to check suitability.

### TECHNICAL CHARACTERISTICS

- Appearance: slightly amber-coloured liquid.
- Density at 20°C: 0.81 ±0.01.
- Flash point: >+61°C.



### PACKAGING

2 litre container.  
5 litre container.  
20 litre container.

### STORAGE

1 year from date of manufacture if stored in unopened original packing in frost-free conditions away from high temperatures and sources of heat.

### WARRANTY

Manufacturer's liability.

### PRECAUTIONS

Read and follow the guidelines in the Health and Safety datasheet for this product.

### TECHNICAL ASSISTANCE

PAREX will, on request, provide information and assistance to companies in relation to the use of a specific product.

Such assistance shall not be associated with structural and design conception, nor assume or accept liability for compliance of substrates, nor compliance to instructions provided.

### Technical Information

**01827 711755**

Download the technical datasheet and consult the health and safety document on our new site: [www.parex.co.uk](http://www.parex.co.uk)