

SAFETY DATA SHEET ACRYLIC MORTAR

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME ACRYLIC MORTAR

SUPPLIER PAREX Ltd
Holly Lane Industrial Estate
Atherstone
Warwickshire
CV9 2QZ
Tel: +44 (0)1827 711755
(Mon-Fri 8:30-16:30)
Fax: +44 (0)1827 711330
sds@parex.co.uk

PRODUCT NO. ACR02, ACR03 (SDS 263)

2 HAZARDS IDENTIFICATION

Irritating to skin. Risk of serious damage to eyes.
CLASSIFICATION (1999/45) Xi;R38, R41.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
CALCIUM HYDROXIDE		1305-62-0	1-5%	Xi;R38,R41.
GGBS		65-99-6	10-30%	Xi;R36/38.
PORTLAND CEMENT	266-043-4	65997-15-1	10-30%	Xi;R38,R41.
SILICA FUME		69012-64-2	1-5%	Xn;R48/20.
SODIUM NITRITE	231-555-9	7632-00-0	< 1%	O;R8 T;R25 N;R50

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

Immediately rinse mouth and provide fresh air. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

ACRYLIC MORTAR

SPILL CLEAN UP METHODS

Avoid generation and spreading of dust. Shovel into dry containers. Cover and move the containers. Flush the area with water.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place. Keep in original container.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
CALCIUM HYDROXIDE	WEL		5 mg/m3			
PORTLAND CEMENT	WEL		4 mg/m3			

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of dust.

RESPIRATORY EQUIPMENT

In case of inadequate ventilation use suitable respirator.

HAND PROTECTION

Wear protective gloves.

EYE PROTECTION

wear suitable safety glasses to EN166

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Granules, Powder
COLOUR	Grey
ODOUR	Odourless
pH-VALUE, CONC. SOLUTION	Approximately 12 to 13 in Aqueous Mix

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Minimise contact with air to avoid degradation.

11 TOXICOLOGICAL INFORMATION

INHALATION

Irritating to respiratory system.

INGESTION

May cause discomfort if swallowed.

ACRYLIC MORTAR**SKIN CONTACT**

Irritating to skin.

EYE CONTACT

Risk of serious damage to eyes.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

MOBILITY

The product hardens to a solid immobile substance.

13 DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

	No transport warning sign required.
ROAD TRANSPORT NOTES	Not Classified
RAIL TRANSPORT NOTES	Not classified.
SEA TRANSPORT NOTES	Not classified.
AIR TRANSPORT NOTES	Not classified.

15 REGULATORY INFORMATION**LABELLING**

Irritant

RISK PHRASES

R38	Irritating to skin.
R41	Risk of serious damage to eyes.

SAFETY PHRASES

S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37/39	Wear suitable gloves and eye/face protection.
S60	This material and its container must be disposed of as hazardous waste.

UK REGULATORY REFERENCES

The Control of Substances Hazardous to Health Regulations 1988.

EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689.

16 OTHER INFORMATION

REVISION DATE

28/01/2011

ACRYLIC MORTAR

REV. NO./REPL. SDS GENERATED 6

SDS NO. 263

RISK PHRASES IN FULL

R8	Contact with combustible material may cause fire.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R36/38	Irritating to eyes and skin.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R25	Toxic if swallowed.
R50	Very toxic to aquatic organisms.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.