

Description:

LED emergency exit sign bollard with acrylic legend panels.
Surface floor mounted with surface cable entry.

Standards:

- EN60598-2-22
- EN55015
- EN50082-1
- EN60555-2
- CE marked

Specification:

Total Weight: 9 Kg.
Voltage / Current: Dependent upon gear: See Table 'AA'.
Dali Versions: Dedicated DALI interface for customer controlled monitoring & reporting. Also, stand alone automatic testing in accordance with IEC62034 if not connected to a DALI system.
Autotest Versions: Stand alone automatic testing in accordance with IEC62034.
Operating Temp: Min 0°C / Max 25°C.
IP Rating: IP65.


Part Numbers Explained:

SHEXP105-AA-B

Where:-

'AA' designates the lamp & gear type.
See Table 'AA' for options & codes.

'B' designates finish.
See Table 'B' for options & codes.



Philip Payne Ltd

A SUBSIDIARY OF F.W. THORPE PLC
Thornhill Road, Lode Lane, Solihull, B91 2HB, England.

Tel: 0121 705 2384
Fax: 0121 711 2469

E-mail: mail@philippayne.co.uk
Website: <http://www.philippayne.co.uk>

Philip Payne Ltd registered in England No. 1361523



ISO 9001
FM55077

Table 'AA': Gear / Operation Options

'AA' Codes	Lamp	Gear / Operation	Supply Current
DL	1W LED strip	220-240V AC 50/60Hz DALI emergency module with self contained 3 hour NiMH battery pack. Maintained or non-maintained operation.	<100mA
LA	1W LED strip	220-240V DC/AC 50/60Hz LED driver for use with central battery or static inverter.	<100mA
LM	1W LED strip	220-240V AC 50/60Hz emergency module with self contained 3 hour NiMH battery pack. Maintained or non-maintained operation.	<100mA
YL	1W LED strip	220-240V AC 50/60Hz Autotest emergency module with self contained 3 hour NiMH battery pack. Maintained or non-maintained operation.	<100mA

Table 'B': Finish Options

'B' Codes	Gear / Operation
G	Grey RAL9006.
K	Black RAL9005.
W	White RAL9010.
V	Old penny bronze.
Z	Special finish: customer specification.

Philip Payne Ltd

A SUBSIDIARY OF F.W. THORPE PLC
Thornhill Road, Lode Lane, Solihull, B91 2HB, England.

Tel: 0121 705 2384

Fax: 0121 711 2469

E-mail: mail@philippayne.co.uk

Website: <http://www.philippayne.co.uk>

Philip Payne Ltd registered in England No. 1361523



ISO 9001
FM55077

