

PROSAFE

A SIMPLISTIC WORK AT HEIGHT SOLUTION

- Non-conductive (100kv/ft)
- Chemical resistant
- Weather resistant
- Spark resistant
- Visible colour
- Non-slip platform deck
- Removable ladder*

The ladder frame can be quickly customised to a plain frame and vice versa. This is cost-effective and offers better stock utilisation.



The Prosafe Tower is a simplistic solution for working at height. It is non-conductive and chemical, weather and spark resistant. Certified and independently tested for use in zone one classified areas, Prosafe is also compliant to 3T assembly processes. With lesser components, the 500-span Prosafe tower is a competitive essential to any access equipment portfolio.

Prosafe ladder frame standard towers, single and double width, 2.0m and 2.5m length to BS 1139 incorporating EN 1004 and WAHR.

Platform height in metres	1.2m	1.7m	2.2m	2.7m	3.2m	3.7m	4.2m	4.7m	5.2m	5.7m	6.2m	6.7m	7.2m	7.7m	8.2m
Platform height in feet	3'10"	5'6"	7'2"	8'10"	10'5"	12'2"	13'8"	15'6"	17'2"	18'10"	20'4"	22'0"	23'7"	25'3"	26'11"

This data sheet is intended as a guide only and as such is not legally binding, nor does it form part of any contract. All dimensions are approximate.



0800 0854161
info@planetplatforms.co.uk
www.planetplatforms.co.uk

Brunel Close, Century Park, Wakefield 41 Industrial Estate, Wakefield WF2 0XG