



STANDARD HANDRAIL:
TO BE MODIFIED BY REMOVING
170 mm FROM REAR
(SMALLER DIAMETER) SECTION,
AS SHOWN HATCHED

VERTICAL SURFACE
(GREATER THAN 400 mm)

A PACKER (ILLUSTRATED) OF APPROX. 50mm WILL BE
REQUIRED WHERE THE VERTICAL FIXING SURFACE EXCEEDS
THE HEIGHT OF THE BACKBOARD TO A POINT WHERE THE
LADDER WOULD FOUL AGAINST THE SURFACE WHEN
STOWED (PACKING SUPPLIED BY OTHERS).

MAXIMUM HEIGHT UP TO 3090 mm
(FLOOR TO BOTTOM OF BACK
MOUNTING BOARD)

NOTE:
IT IS RECOMMENDED THAT THE MINIMUM STRUCTURAL OPENING LENGTH
IS 1000 mm FOR AN ELITE STAIRWAY INSTALLED WITH A HANDRAIL.

PREMIER LOFT LADDERS
2 Dawson Drive
Trimley St. Mary
Felixstowe
Suffolk
IP11 0YW

www.premierloftladders.co.uk
Tel: 0845 9000 195
Fax: 01394 214413



Issue	Description	Date	Name
B	Logo change	08/2014	J.P.
A	Addition of packer text	09/2013	J.P.
	First issue	10/2012	J.P.

Drawing Title:
**ELITE STAIRWAY: 11 treads
FITTING TO VERTICAL
SURFACE >400mm**

Scale:
1:1
Sheet:
PLOT AT
A3 1:5
Issue:

All dimensions in mm
© All rights reserved Report all discrepancies Do not scale drawings
Filename: ELITE11 HANDRAIL.DWG Project: Standard Issue

NOTE: ALL INFORMATION CONTAINED IN THIS DOCUMENT IS STRICTLY CONFIDENTIAL.
THIS DRAWING IS THE PROPERTY OF PREMIER LOFT LADDERS AND MUST NOT BE REPRODUCED WITHOUT PRIOR PERMISSION.