



A PACKER (ILLUSTRATED) OF APPROX. 50mm WILL BE REQUIRED WHERE THE VERTICAL FIXING SURFACE EXCEEDS THE HEIGHT OF THE BACKBOARD TO A POINT WHERE THE LADDER WOULD FOUL AGAINST THE SURFACE WHEN STOWED (PACKING SUPPLIED BY OTHERS).

MAXIMUM HEIGHT UP TO 3390 mm
(FLOOR TO BOTTOM OF BACK MOUNTING BOARD)

NOTE:
IT IS RECOMMENDED THAT THE MINIMUM STRUCTURAL OPENING LENGTH IS 1000 mm FOR AN ELITE STAIRWAY INSTALLED WITH A HANDRAIL.

PREMIER LOFT LADDERS
2 Dawson Drive
Trimley St. Mary
Felixstowe
Suffolk
IP11 0YW

www.premierloftladders.co.uk
Tel: 0845 9000 195
Fax: 01394 214413



Issue	Description	Date	Name
B	Logo change	08/2014	J.P.
A	Addition of packer text	09/2013	J.P.
	First issue	10/2012	J.P.

Drawing Title:		Scale:
FITTING STANDARD HANDRAIL TO ELITE STAIRWAY: 12 treads		1:1
All dimensions in mm		Sheet: PLOT AT A3 1:5
© All rights reserved Report all discrepancies Do not scale drawings		Issue:
Filename: ELITE12 HANDRAIL.DWG	Project: Standard Issue	

NOTE: ALL INFORMATION CONTAINED IN THIS DOCUMENT IS STRICTLY CONFIDENTIAL. THIS DRAWING IS THE PROPERTY OF PREMIER LOFT LADDERS AND MUST NOT BE REPRODUCED WITHOUT PRIOR PERMISSION.