



STANDARD HANDRAIL:  
TO BE MODIFIED BY REMOVING  
170 mm FROM REAR  
(SMALLER DIAMETER) SECTION,  
AS SHOWN HATCHED

VERTICAL SURFACE  
(GREATER THAN 400 mm)

A PACKER (ILLUSTRATED) OF APPROX. 50mm WILL BE  
REQUIRED WHERE THE VERTICAL FIXING SURFACE EXCEEDS  
THE HEIGHT OF THE BACKBOARD TO A POINT WHERE THE  
LADDER WOULD FOUL AGAINST THE SURFACE WHEN  
STOWED (PACKING SUPPLIED BY OTHERS).

MAXIMUM HEIGHT UP TO 3390 mm  
(FLOOR TO BOTTOM OF BACK  
MOUNTING BOARD)

NOTE:  
IT IS RECOMMENDED THAT THE MINIMUM STRUCTURAL OPENING LENGTH  
IS 1000 mm FOR AN ELITE STAIRWAY INSTALLED WITH A HANDRAIL.

PREMIER LOFT LADDERS  
2 Dawson Drive  
Trimley St. Mary  
Felixstowe  
Suffolk  
IP11 0YW  
  
www.premierloftladders.co.uk  
Tel: 0845 9000 195  
Fax: 01394 214413



| Issue | Description             | Date    | Name |
|-------|-------------------------|---------|------|
| B     | Logo change             | 08/2014 | J.P. |
| A     | Addition of packer text | 09/2013 | J.P. |
|       | First issue             | 10/2012 | J.P. |

Drawing Title:  
**ELITE STAIRWAY: 12 treads  
FITTING TO VERTICAL  
SURFACE >400mm**

Scale:  
**1:1**  
Sheet:  
PLOT AT  
A3 1:5  
Issue:

All dimensions in mm  
© All rights reserved Report all discrepancies Do not scale drawings  
Filename: ELITE12 HANDRAIL.DWG Project: Standard Issue