



STANDARD HANDRAIL:
TO BE MODIFIED BY REMOVING
170 mm FROM REAR
(SMALLER DIAMETER) SECTION,
AS SHOWN HATCHED

VERTICAL SURFACE
(GREATER THAN 400 mm)

A PACKER (ILLUSTRATED) OF APPROX. 50mm WILL BE
REQUIRED WHERE THE VERTICAL FIXING SURFACE EXCEEDS
THE HEIGHT OF THE BACKBOARD TO A POINT WHERE THE
LADDER WOULD FOUL AGAINST THE SURFACE WHEN
STOWED (PACKING SUPPLIED BY OTHERS).

MINIMUM CLEARANCE 715 mm

MAXIMUM HEIGHT UP TO 2500 mm
(FLOOR TO BOTTOM OF BACK
MOUNTING BOARD)

NOTE:
IT IS RECOMMENDED THAT THE MINIMUM STRUCTURAL OPENING LENGTH
IS 1000 mm FOR AN ELITE STAIRWAY INSTALLED WITH A HANDRAIL.

PREMIER LOFT LADDERS
2 Dawson Drive
Trimley St. Mary
Felixstowe
Suffolk
IP11 0YW

www.premierloftladders.co.uk
Tel: 0845 9000 195
Fax: 01394 214413



Issue	Description	Date	Name
B	Logo change	08/2014	J.P.
A	Addition of packer text	09/2013	J.P.
	First issue	10/2012	J.P.

Drawing Title:
**ELITE STAIRWAY: 9 treads
FITTING TO VERTICAL
SURFACE >400mm**

Scale:
1:1
Sheet:
PLOT AT
A3 1:5
Issue:

All dimensions in mm
© All rights reserved Report all discrepancies Do not scale drawings
Filename: ELITE9 VERT HANDRAIL.DWG Project: Standard Issue

NOTE: ALL INFORMATION CONTAINED IN THIS DOCUMENT IS STRICTLY CONFIDENTIAL.
THIS DRAWING IS THE PROPERTY OF PREMIER LOFT LADDERS AND MUST NOT BE REPRODUCED WITHOUT PRIOR PERMISSION.