



Supreme with wooden hatchbox for flat roofs, 3 additional treads

Ready to install element

Safety tested: tested according to DIN EN 14975 by TÜV Süd

Airtightness (a value): class 4 - 600pa pressure tested to DIN EN 12207 by ift Rosenheim

Thermal properties: U - Value lower cover = 0.8 W/m² K
U - Value top cover (see table below)

Calculation of the isolated area according to DIN EN ISO 6946 by manufacturer

Stairs:

Scissor unit: die-cast aluminium

Load bearing capacity per tread 200 kg or 500 kg / m² of the entire component
Tread depth 14 cm (16 cm)

Custom sizes:

Custom sizes are available on request

Treads	Aperture size (length)	Space required in cm		
		Floor to ceiling height "A"	Setdown point "B"	Swivel range "C"
9	127.5 - 197	220 - 250	165 - 153	173
10	127.5 - 197	251 - 279	176 - 163	186
11	137.5 - 197	280 - 309	187 - 173	198
12	137.5 - 197	310 - 339	198 - 183	210
13	167.5 - 197	340 - 369	225 - 212	237
14	177.5 - 197	370 - 399	238 - 224	251
15	187.5 - 197	400 - 430	249 - 235	264

Hatchbox external dimensions = aperture size - 1.5cm

Top cover thermal insulation values		
Insulation installed on site "D" max.	U - Value W/m ² K	Seal type
27 mm	1.1	Single seal
40 mm	0.68	Double seal
80 mm	0.38	Double seal
100 mm	0.31	Double seal



PREMIER LOFT LADDERS
2 Dawson Drive,
Trimley St Mary,
Felixstowe, Suffolk. IP11 0YW
Tel: 0845 9000 195
Fax: 01394 214413
www.premierloftladders.co.uk



© All rights reserved. Report all discrepancies. Do not scale drawings.

Rev	Date	Name	Scale
A	02.10.2012	Ra	1:10
B	14.09.2013	JP	
C	10.08.2014	JP	

Other sizes and different ceiling heights are available on request

6000213

Supreme with wooden hatchbox for flat roofs, 3 additional treads
The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.