



Supreme with steel hatchbox F30

Ready to install element

Safety tested: tested according to DIN EN 14975 by TÜV Süd

Thermal properties: U - Value lower cover F30 = 0.57 W/m² K

Calculation of the isolated area according to DIN EN ISO 6946 by manufacturer

Stairs:

Scissor unit: die-cast aluminium

Load bearing capacity per tread 200 kg or 500 kg / m² of the entire component

Tread depth 14 cm (16 cm)

Custom sizes:

Custom sizes are available on request

Aperture length depends on the number of treads		Space required in cm		
Treads	Aperture size (length)	Floor to ceiling height "A"	Setdown point "B"	Swivel range "C"
9	100 - 150	220 - 250	127 - 122	130
10	100 - 150	250 - 279	137 - 133	141
11	100 - 150	279 - 309	148 - 143	152
12	100 - 150	309 - 339	159 - 154	164
13	130 - 150	339 - 369	186 - 182	190
14	140 - 150	369 - 399	199 - 194	202
15	150 - 150	399 - 430	211 - 206	215

Hatchbox external dimensions = aperture size - 1.5cm

Standard sizes	
Aperture size length x width	Tread width
120 x 60 cm	20 cm
120 x 70 cm	30 cm
130 x 70 cm	30 cm
140 x 70 cm	30 cm



PREMIER LOFT LADDERS
2 Dawson Drive,
Trimley St Mary,
Felixstowe, Suffolk. IP11 0YW
Tel: 0845 9000 195
Fax: 01394 214413
www.premierloftladders.co.uk



© All rights reserved. Report all discrepancies. Do not scale drawings.

First issue	Date	Name	Scale
A	31.01.2013	Ra	Supreme with steel hatchbox F30 1:10
B	14.09.2013	JP	
	10.08.2014	JP	

Other sizes and different ceiling heights are available on request

6000227

The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.

NOTE: ALL INFORMATION CONTAINED IN THIS DOCUMENT IS STRICTLY CONFIDENTIAL. THIS DRAWING IS THE PROPERTY OF PREMIER LOFT LADDERS AND MUST NOT BE REPRODUCED WITHOUT PRIOR PERMISSION.