

DECLARATION OF PERFORMANCE

N° 2013062503


1. Product-type:
High Pressure compact laminate ProdEX FIREPROOF (Thickness: 8 - 22 mm)
2. Name & contact address of the manufacturer:
Prodema,s.a.
B° San Miguel 9
20.250 Legorreta (Spain)
3. Intended use of the construction product:
As external finishes in walls or ceilings, subject to reaction to fire regulations
4. System of assessment and verification of the constancy of performance: 1
5. Notified body:
 - Tecnalía R&I Certificación NB 1239
 - Evaluation of the Factory Production Control
 - Reaction to fire for initial type testing
 - System 1
 - Certificate of constancy of performance of the product N° 1239/CPR/0801106 dated the 4th of July 2012

6. Declared performance:

Essential characteristics	Performance	Harmonized technical specifications
Reaction to fire	B-s1;d0	EN 438-7:2005
Resistance to fire	NPD	
Water vapour permeability	110 250	
Wet cup Dry cup		
Resistance to fixings	3.000 N 4.000 N	
8 mm hickness ≥ 10 mm thickness		
Direct airborne sound insulation	NPD	
Bonding Strength	NPD ¹	
Flexural tensile strength	PASS	
Thermal conductivity	≤ 0,3 w / m * k	
Content of pentachloropenol	NPD ¹	
Release of formaldehyde	NPD ²	
Sound absorption	NPD ²	
Thermal shock resistance	PASS	
Durability: Resistance to wet conditions	PASS	
Durability: Density	PASS	
¹ Applicable only to HPL composite panles		
² Applicable only to panels intended for internal use		

- The performance of the product identified in point 1 is in conformity with the declared performance in point 6
- This declaration performance is issued under the sole responsibility of the manufacturer identified in point 2
- Signed for and on behalf of the manufacturer by: Iñigo Beistegui (Sales Manager)

Signature:



Place and date of issue:

Legorreta, the 19th of May 2.014

