

**DECLARATION OF PERFORMANCE**  
N° 2013062502

1. Product-type:  
High Pressure compact laminate ProdEX IGN (Thickness: 6 - 22 mm)
2. Name & contact address of the manufacturer:  
Prodema,s.a.  
B° San Miguel 9  
20.250 Legorreta (Spain)
3. Intended use of the construction product:  
As external finishes in walls or ceilings, subject to reaction to fire regulations
4. System of assessment and verification of the constancy of performance: 1
5. Notified body:
  - Tecnalía R&I Certificación NB 1239
  - Evaluation of the Factory Production Control
  - Reaction to fire for initial type testing
  - System 1
  - Certificate of constancy of performance of the product N° 1239/CPR/0801101 dated the 30<sup>th</sup> of June 2006

6. Declared performance:

Essential characteristics	Performance	Harmonized technical specifications
Reaction to fire	B-s2;d0	EN 438-7:2005
Resistance to fire	NPD	
Water vapour permeability		
Wet cup	110	
Dry cup	250	
Resistance to fixings		
6mm thickness	2.000 N	
8 mm thickness	3.000 N	
≥ 10 mm thickness	4.000 N	
Direct airborne sound insulation	NPD	
Bonding Strength	NPD <sup>1</sup>	
Flexural tensile strength	PASS	
Thermal conductivity	≤ 0,3 w / m * k	
Content of pentachloropenol	NPD <sup>1</sup>	
Release of formaldehyde	NPD <sup>2</sup>	
Sound absorption	NPD <sup>2</sup>	
Thermal shock resistance	PASS	
Durability: Resistance to wet conditions	PASS	
Durability: Density	PASS	

<sup>1</sup> Applicable only to HPL composite panels  
<sup>2</sup> Applicable only to panels intended for internal use

- The performance of the product identified in point 1 is in conformity with the declared performance in point 6
- This declaration performance is issued under the sole responsibility of the manufacturer identified in point 2
- Signed for and on behalf of the manufacturer by: Iñigo Beistegui (Sales Manager)

Signature:



Place and date of issue:

Legorreta, the 19<sup>th</sup> of May 2.014