

Corner bumper For wash basin V240

Cleaning

Use a mild detergent and a soft cloth or brush. Clean gently, without scratching the product. Rinse well and wipe dry. For tough dirt, several treatments may be required. Do not let water or other liquids to dry on the surface, which may result in a gray coating or stains. Avoid prolonged contact with chlorine or acidic cleaner, silver polish or food products this may cause burn marks.

Stains & discoloration

Use small amounts of a polishing agent suitable for stainless steel and rub the surface gently just on the spot. Always rub countertop surfaces in the grinding direction, other surfaces with circular movements. Do not use steel wool, which not only scratches the surface, but also may leave small particles on the surface that can develop into rust spots and which later can turn into rust. Heavy limescale can be removed with vinegar (10%). Rinse thoroughly and dry immediately. Polishing with chalk on a soft cloth can make dull areas shiny again.

If you have any further questions, please contact us at +46 10 41 44 900.

Screw installation

1. Put the bumper on the wash basin and do a marking in the holes.
2. Remove the bumper.
3. Drill a hole with $\text{Ø}3,3$.
4. Thread the hole with a M4 tap.
5. Install the bumper and screw the screws by hand.
6. Fit the cover to the screws.

Glued installation

It is also possible to glue the bumper, make sure to follow the glue suppliers instructions.

Installation step by step

Screwed installation

