



**RCM LIMITED**  
**MATERIAL SAFETY DATA SHEET**

**Date Prepared:** January 13, 2003  
UAC Fibre Cement Building Products

**Date revised:** 12<sup>th</sup> July 2013 (3<sup>rd</sup> edition)  
**MSDS No:** UAC003

**1. Identification of the substance/mixture and of the company/undertaking;**

**Tel.** 0845 130 3725

**Email:** [info@rcmltd.biz](mailto:info@rcmltd.biz)

**Address:** Unit 27 Rosevale Road  
Parkhouse Industrial Estate West  
Newcastle under Lyme  
Staffordshire  
ST5 7EF

**Product Name:** RCM Supertech

**Other Names:** Fibre Cement, Fibre reinforced cement

**Uses/Applications:** The above products are used as internal/external wall cladding, ceiling, roofing, flooring and fencing.

**2. Hazards identification;**

The fibre cement products in their intact state do not present a hazard. However, one should be aware of the ill-effect and danger from prolonged exposure to the air-borne dust generated through cutting, drilling, routing, sawing and crushing of the fibre cement products if the correct respiratory protective equipment is not worn.

*Acute Effects*

**Skin condition:** The dust from this product may cause irritation of the skin from friction but is not absorbed through the skin.

**Eye contact:** The dust from this product may irritate the eyes causing watering and redness.  
**Ingestion:** Unlikely under normal conditions of use, but ingestion of the dust from this product may result in abdominal discomfort.

**Inhaled:** The dust from this product may cause irritation of nose, throat and lungs causing coughing and sneezing.

*Chronic Effects*

**Inhaled:** Prolonged and continuous exposure (without the correct respiratory protective equipment, over a number of years) to significant, airborne, respirable dust levels containing crystalline silica may cause bronchitis, silicosis and lung cancer.

### 3. Composition/information on ingredients;

Ingredient	CAS Number	Composition	R-Phrase
Ordinary Portland Cement	65997-15-1	20-40%	R36 R37 R38
Crystalline Silica (Quartz)	14808-60-7	20-50%	-
Cellulose	9004-34-6	<10%	-
Other non-hazardous ingredients such as pigment, fillers and surface coatings.	-	<10%	-

Note: All the fibre cement products consist of cellulose fibre from wood pulp only and do not contain asbestos.

### 4. First-aid measures;

Skin contact:	Wash thoroughly with mild soap and water.
Eye contact:	Flush with running water.
Ingestion:	Not expected under normal condition of use. Drink plenty of water.
Inhaled:	Remove to fresh air.

Note: Seek medical attention if symptom persisted.

### 5. Fire-fighting measures;

Note: The fibre cement products will not burn or help in burning, thus no specific fire fighting measures is required. In case of fire, extinguish with carbon dioxide, water, foam or dry chemical as for surrounding materials.

### 6. Accidental release measures;

Note: Not applicable

### 7. Handling and storage;

Note: There are no specific requirements for handling and storage.

### 8. Exposure controls/personal protection;

Exposure Standards – Occupational Safety and Health Act 1994 – Occupational Safety and Health (Use and Standards of Exposure of Chemical Hazardous to Health) Regulations 2000, Malaysia.

Crystalline Silica (Quartz)	0.1mg/m <sup>3</sup> time-weighted average (TWA) as respirable dust
Calcium Silicate (Synthetic)	010mg/m <sup>3</sup> time-weighted average (TWA) as respirable dust
Cellulose (Wood fibre)	10mg/m <sup>3</sup> time-weighted average (TWA) as respirable dust

Note: Where a state or local authority prescribes a lower standard, the lower standard applies.

General Controls:	Avoid generating dust or keep exposure to dust as low as practicable. Work areas should be cleaned regularly by wet sweeping or vacuuming.
Engineering Controls:	Practices likely to generate dust should be carried out in adequately ventilated areas or in process enclosures with exhaust ventilation.

#### Personal Protection:

Eye protection:	Safety goggles/glasses should be worn.
Skin Protection:	Direct contact with dust and debris should be avoided by wearing long sleeved shirts or gloves.
Inhalation protection:	During dry cutting, drilling, routing, and sanding with power or abrasive tool, or if dust is generated, use an approved particulate dust mask.

## 9. Physical and chemical properties;

Appearance: Greyish or pinkish solid boards or planks or coated with various flat or corrugated profile with standard sizes.

Odour:	-	pH:	-
Boiling point:	-	Melting point:	-
Flashpoint:	-	Explosive property:	-
Vapour pressure:	-	Specific gravity:	-
Solubility in water:	Not soluble in water		

## 10. Stability and reactivity;

Note: Fibre cement products are generally dimensionally stable and non-reactive, resistant to rot and water damage in their normal scope of application.

## 11. Toxicological information;

Note: Not applicable

## 12. Ecological Information

Note: Not applicable

## 13. Disposal considerations;

Note: Waste may be disposed by landfill; however disposal should comply with the local authority requirements.

## 14. Transport information;

Note: There are no specific requirements for transportation handling.

## 15. Regulatory information; Note: Not applicable

## 16. Other information.

The fibre cement products contain crystalline silica which is classified as hazardous substance according to the criteria of Malaysia Occupational safety and Health Act 1994 – Occupational Safety and Health (Use and Standards of Exposure of Chemical Hazardous to Health) Regulations 2000. Breathing in fine silica dust when working with products is hazardous and may cause bronchitis, silicosis or cancer.

MINIMISE DUST GENERATION AND DO NOT BREATH DUST! Operators must wear approved particulate dust mask when power tools used.

### Disclaimer

The information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of product.

Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose.