

Technical Information Sheet Article No. 2141

Color Paste

Coloured paste for tinting Adolit wood preservative salts.

Range of use

Adolit Color Paste is used for tinting Adolit fixating wood preservative salts in large scale procedures such as open tank steeping and impregnation of post bases as well as pressure impregnation procedures.

It is especially suitable for wood used in outdoor areas such as fences, palisades, wood siding and other building elements for garden and landscaping as well as in agriculture.

Property profile

Lightfast and weather proof coloured paste for tinting wood with a scumble effect. Water dilutable, high yielding, does not settle.

Production of the solution

Adolit Color Paste is stirred thoroughly into the ready salt solution in a concentration of 0.2-1 %, depending on the desired intensity of colour.

Characteristic data of the product

Density:	approx. 1.07 g/cm ³
Odour:	light
pH-Value:	6-8
Packaging:	5 kg and 25 kg plastic containers
Colours:	brown Art. No. 2141
	red Art. No. 2144
	green Art. No. 2145

Notes

Before treated wood is used in outdoor areas, the fixation time required for the salts must be strictly observed to prevent preservative constituents that have not thoroughly dried from being leached out by rain.

Shelf-life

At least one year in closed, original containers, stored dry and frost-free.

Safety data

Observe the usual precautionary measures when working and for storage

Disposal

Dispose of product remains in compliance with valid regulations. Completely empty containers should be recycled.

Ecology

Do not lead into aquatic environments, the sewer system or the ground. Water Hazard Class 1

Labelling

Flammability class	-/-
Regulations on Hazardous substances	-/-
GGVS/ADR	-/-

The statements above are compiled from our field of production and according to the latest technological developments and application techniques.

Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid. With the publication of this Technical Information Sheet all previous editions are no longer valid.



Remmers (UK) Limited Crawley
United Kingdom
Tel: +44 (0) 1293 594 010
Fax: +44 (0) 1293 594 037
www.remmers.co.uk