



Technical Data Sheet
Art. No. 4551

Copper Tape

Self-adhesive copper tape in the
SL Floor WHG AS system (Z-59.12-303 DIBt)

Range of use

Self-adhesive copper tape for discharging electrical charges in conductive coating systems

Substrate

The primed substrate to which a scratch coat has been applied must be even, clean, dry and free of substances that could interfere with adhesion.

Directions

Attach self-adhesive Copper Tape in a grid or as a loop line and lead to potential equalisation.

Make sure that no point of the surface is more than 10 m away from the next copper tape.

Characteristic data of the product

Appearance: metallic copper tape

Connection to potential equalisation should be executed by an authorised, specialist company.

Packaging, application rate, shelf-life

Packaging:
Roll: 16.5 m

Application rate:
approx. 0.5 - 1.0 m/m²

Shelf-life:
Unlimited shelf-life when stored dry.

Safety, ecology, disposal

Further information on safety when transporting, storing and handling as well as disposal and ecology is found in the latest Safety Data Sheet.

Emergency information:

Mon.- Thurs. from 7:30 a.m. to 4:00 p.m.; Fri. 7:30 a.m. to 2:00 p.m.
Product Safety Department:
Tel.: +49 (0)5432/83-138
After office hours:
Giftinformationszentrum-Nord (Poison Centre) 24 h hotline
+ 49(0)551 - 19240

The statements above are compiled from our field of production and according to the latest technological developments and application techniques.

Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid. With the publication of this Technical Information Sheet all previous editions are no longer valid.



Remmers (UK) Limited Crawley
United Kingdom
Tel: +44 (0) 1293 594 010
Fax: +44 (0) 1293 594 037
www.remmers.co.uk