

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2018

Version number 5

Revision: 19.04.2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **EPOXY ST 100 TX KOMPONENTE A**

Article number: 1157

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating

Uses advised against No further relevant information available.

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

Remmers GmbH  
Postfach 1255  
D-49624 Lönningen / Germany  
Tel.: +49(0)5432/83-0  
Fax: +49(0)5432/3985

Remmers (UK) Limited  
Unit B1 The Fleming Centre  
West Sussex RH10 9NN  
fon +44 (0) 1293 594 010  
fax +44 (0) 1293 594 037

##### Informing department:

Product Safety department: Tel.: Steve Dunn Tel.: +44 (0) 1293 594 010  
E-Mail: sales@remmers.co.uk

#### 1.4 Emergency telephone number:

during working hours:

U.K.: Tel.: +44 (0) 1293 594 010

sales@remmers.co.uk

Head Office Germany: Tel.: +49 (0)5432 83 187

info@remmers.de

after working hours: Tel.: +49 (0)171 21 34 091

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300

outside USA and Canada: 001-703-527-3887

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

##### Hazard pictograms



GHS07 GHS09

Signal word Warning

(Contd. on page 2)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2018

Version number 5

Revision: 19.04.2018

Trade name **EPOXY ST 100 TX KOMPONENTE A**

(Contd. of page 1)

**Hazard-determining components of labelling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)  
 oxirane, mono[(C12-14-alkyloxy)methyl] derivs  
 Phenol, methylstyrenated

**Hazard statements**

H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H317 May cause an allergic skin reaction.  
 H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P103 Read label before use.  
 P264 Wash thoroughly after handling.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P337+P313 If eye irritation persists: Get medical advice/attention.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures****Description:** Modified epoxide resin

<b>Dangerous components:</b>		
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-XXXX	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	60-80%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4 Reg.nr.: 01-2119485289-22-XXXX	oxirane, mono[(C12-14-alkyloxy)methyl] derivs Skin Irrit. 2, H315; Skin Sens. 1, H317	5-10%
CAS: 68512-30-1 EINECS: 270-966-8 Reg.nr.: 01-2119555274-38-XXXX	Phenol, methylstyrenated Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	5-10%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-XXXX	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Eye Irrit. 2, H319	2.5-5%

**Additional information** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information**

If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally.

**After inhalation**

Use a respiration bag or breathing device.  
 Supply fresh air and call for doctor for safety reasons.  
 In case of unconsciousness bring patient into stable side position for transport.

**After skin contact**

If skin irritation continues, consult a doctor.  
 Wash immediately with water and soap and rinse thoroughly.

(Contd. on page 3)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2018

Version number 5

Revision: 19.04.2018

Trade name **EPOXY ST 100 TX KOMPONENTE A**

(Contd. of page 2)

**After eye contact**

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

**After swallowing** Seek immediate medical advice.**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents**

Water spray jet

Carbon dioxide

Foam

Use fire fighting measures that suit the environment.

**5.2 Special hazards arising from the substance or mixture**

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen chloride (HCl)

further harmful conflagration gases and fumes

**5.3 Advice for firefighters****Protective equipment:** Wear self-contained breathing apparatus.**Additional information**

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

**6.2 Environmental precautions:**

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

**6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling** Use only in well ventilated areas.**7.2 Conditions for safe storage, including any incompatibilities****Storage****Requirements to be met by storerooms and containers:** Prevent any penetration into the ground.**Information on storage in a common storage facility:**

Store away from oxidising agents.

Store away from food.

**Further information about storage conditions:**

Store container in a well ventilated position.

Protect from frost.

Keep container tightly closed.

**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2018

Version number 5

Revision: 19.04.2018

Trade name **EPOXY ST 100 TX KOMPONENTE A**

(Contd. of page 3)

**8.1 Control parameters****Components with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with limit values that have to be monitored at the workplace.

**Additional information:** The lists that were valid during compilation were used as a basis.

**8.2 Exposure controls****Personal protective equipment****General protective and hygienic measures**

Do not eat, drink or smoke while working.  
 Use skin protection cream for preventive skin protection.  
 Keep away from food, beverages and animal feed.  
 Immediately remove soiled, saturated clothing.  
 Wash hands before pauses and after work.  
 Avoid contact with eyes and skin.

**Respiratory equipment:**

Filter A (brown)

Only use ambient air independent respiratory equipment in pits, shafts and silos!

**Protection of hands:**

Long cuffed gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:** Tightly sealed safety glasses.

**Body protection:** Protective work clothing.

## SECTION 9: Physical and chemical properties

**9.1 Information on basic physical and chemical properties****General Information****Appearance:**

<b>Form:</b>	Fluid
<b>Colour:</b>	Whitish
<b>Odour:</b>	Weak, characteristic
<b>Odour threshold:</b>	Not determined.

**pH-value:** Not determined.

**Change in condition**

<b>Melting point/freezing point:</b>	Not determined
<b>Initial boiling point and boiling range:</b>	> 200 °C

**Flash point:** Not applicable

**Inflammability (solid, gaseous)** Not applicable.

**Ignition temperature:** > 450 °C

**Decomposition temperature:** Not determined.

**Self-inflammability:** Product is not self-igniting.

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2018

Version number 5

Revision: 19.04.2018

Trade name **EPOXY ST 100 TX KOMPONENTE A**

(Contd. of page 4)

<b>Explosive properties:</b>	Product is not explosive.
<b>Explosive Limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
<b>Vapour pressure:</b>	Not determined.
<b>Density</b>	Not determined
<b>Relative density</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>Evaporation rate</b>	Not determined.
<b>Solubility in / Miscibility with</b>	
<b>Water:</b>	Not miscible or difficult to mix
<b>Distribution coefficient (n-octanol/water):</b>	Not determined.
<b>Viscosity:</b>	
<b>dynamic:</b>	Not determined.
<b>kinematic:</b>	Not determined.
<b>Solvent separation test</b>	< 3 %
<b>9.2 Other information</b>	No further relevant information available.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

### 10.2 Chemical stability

**Thermal decomposition / conditions to be avoided:**

No decomposition if handled and stored according to specifications.

**10.3 Possibility of hazardous reactions** Exothermic polymerisation

**10.4 Conditions to avoid** No further relevant information available.

**10.5 Incompatible materials:** No further relevant information available.

### 10.6 Hazardous decomposition products:

None if used properly.

None if stored properly.

May be released in fire:

Carbon monoxide and carbon dioxide

Hydrogen chloride (HCl)

Phenol

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

**Acute toxicity:** Based on available data, the classification criteria are not met.

#### LD/LC50 values that are relevant for classification:

##### ATE (Acute Toxicity Estimates)

Oral	LD50	35,325 mg/kg (rat)
Dermal	LD50	57,438 mg/kg (rabbit)
Inhalative	LC50/4 h	61.7 mg/l

#### CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

Oral	LD50	>10,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

#### CAS: 68512-30-1 Phenol, methylstyrenated

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	5 mg/l (rat)

### Skin corrosion/irritation:

Causes skin irritation.

(Contd. on page 6)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2018

Version number 5

Revision: 19.04.2018

Trade name **EPOXY ST 100 TX KOMPONENTE A**

(Contd. of page 5)

**Serious eye damage/irritation:**

Causes serious eye irritation.

**Sensitisation:**

May cause an allergic skin reaction.

**Germ cell mutagenicity:** Based on available data, the classification criteria are not met.**Carcinogenicity:** Based on available data, the classification criteria are not met.**Reproductive toxicity:** Based on available data, the classification criteria are not met.**STOT-single exposure:** Based on available data, the classification criteria are not met.**STOT-repeated exposure:** Based on available data, the classification criteria are not met.**Aspiration hazard:** Based on available data, the classification criteria are not met.**SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity:** No further relevant information available.**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**Ecotoxicological effects:****Remark:** Toxic for fish**Additional ecological information:****General notes:**

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Also toxic for fish and plankton in bodies of water.

Toxic for aquatic organisms

**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****Recommendation**

Not hardened material must be disposed of as hazardous waste according to official regulations.

Hardened product remains may be disposed of as building rubble or put into household garbage.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

**European waste catalogue**

20 01 28 | paint, inks, adhesives and resins other than those mentioned in 20 01 27

**Uncleaned packaging:****Recommendation:**

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

**SECTION 14: Transport information****14.1 UN-Number****ADR, IMDG, IATA**

UN3082

**14.2 UN proper shipping name****ADR**3082 ENVIRONMENTALLY HAZARDOUS  
SUBSTANCE, LIQUID, N.O.S. (reaction product:  
bisphenol-A-(epichlorhydrin) epoxy resin (number  
average molecular weight = 700))**IMDG**ENVIRONMENTALLY HAZARDOUS SUBSTANCE,  
LIQUID, N.O.S. (reaction product: bisphenol-A-  
(epichlorhydrin) epoxy resin (number average  
molecular weight = 700)), MARINE POLLUTANT

(Contd. on page 7)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2018

Version number 5

Revision: 19.04.2018

Trade name **EPOXY ST 100 TX KOMPONENTE A**

(Contd. of page 6)

<b>IATA</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700))
<b>14.3 Transport hazard class(es)</b>	
<b>ADR</b>	
<b>Class</b>	9 (M6) Miscellaneous hazardous substances and articles.
<b>Label</b>	9
<b>IMDG, IATA</b>	
<b>Class</b>	9 Miscellaneous hazardous substances and articles.
<b>Label</b>	9
<b>14.4 Packing group</b>	
<b>ADR, IMDG, IATA</b>	III
<b>14.5 Environmental hazards:</b>	
<b>Marine pollutant:</b>	Yes
	Symbol (fish and tree)
<b>Special marking (ADR):</b>	Symbol (fish and tree)
<b>Special marking (IATA):</b>	Symbol (fish and tree)
<b>14.6 Special precautions for user</b>	Warning: Miscellaneous hazardous substances and articles.
<b>hazard identification number:</b>	90
<b>EMS Number:</b>	F-A,S-F
<b>Stowage Category</b>	A
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
<b>Transport/Additional information:</b>	
<b>ADR</b>	
<b>Limited quantities (LQ)</b>	5L
<b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>Transport category</b>	3
<b>IMDG</b>	
<b>Limited quantities (LQ)</b>	5L
<b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>UN "Model Regulation":</b>	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT = 700)), 9, III

(Contd. on page 8)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 19.04.2018

Version number 5

Revision: 19.04.2018

Trade name **EPOXY ST 100 TX KOMPONENTE A**

(Contd. of page 7)

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Directive 2012/18/EU

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category** E2 Hazardous to the Aquatic Environment

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

### Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

**Department issuing data specification sheet:** Product Safety department / EHS

### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3