

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

Name of the product

MS 150

No.: GBI F 039-2

Unique identification code of the product-type:

7505

[

Intended use/es:

**Sealant for facade for interior and exterior application
(intended for use in cold climates)
EN 15651-1: F-EXT-INT-CC**

Manufacturer:

**Remmers GmbH
Bernhard-Remmers-Str. 13
49624 Lönigen / Germany**

System/s of AVCP:

**System 3
System 3 for reaction to fire**

Harmonised standard:

EN 15651-1:2012

Notified body/ies:

**ift Rosenheim GmbH
83026 Rosenheim / Germany
Kennnummer 0757**

Declared performance/s:

Conditioning: Method B
 Substrate: Anodised aluminium and mortar M1
 Pre-treatment: Adhesion promoter

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 10 %		
Tensile properties at maintained extension after water immersion	NF		
Tensile properties (i.e. secant modulus)	≤ 0,9 MPa		
Tensile properties (i.e. at maintained extension)	NF		
Durability	passed		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Remmers GmbH
 i. A. Stephanie Braak
 Head of laboratory sealants

Löningen, 01.11.2016.....

S Braak.....
 (signature)