

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.03.2019

Version number 6

Revision: 06.03.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **PRIMER PUR**

Article number: 7530

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC10 Roller application or brushing

Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

ERC10a Widespread use of articles with low release (outdoor)

ERC11a Widespread use of articles with low release (indoor)

Application of the substance / the mixture Priming

Uses advised against No further relevant information available.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH

Postfach 1255

D-49624 Lönningen / Germany

Tel.: +49(0)5432/83-0

Fax: +49(0)5432/3985

Information department:

Product Safety department: Tel.: Steve Dunn Tel.: +44 (0) 1293 594 010

E-Mail: sales@remmers.co.uk

Remmers (UK) Limited
Unit B1 The Fleming Centre
West Sussex RH10 9NN
fon +44 (0) 1293 594 010
fax +44 (0) 1293 594 037

1.4 Emergency telephone number:

during working hours:

U.K.: Tel.: +44 (0) 1293 594 010

sales@remmers.co.uk

Head Office Germany: Tel.: +49 (0)5432 83 187

info@remmers.de

after working hours: Tel.: +49 (0)171 21 34 091

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300

outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Sens. 1 H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.03.2019

Version number 6

Revision: 06.03.2019

Trade name **PRIMER PUR**

(Contd. of page 1)

STOT SE 3 H335 May cause respiratory irritation.
 Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02 GHS07

Signal word Warning**Hazard-determining components of labelling:**

aliphatic polyisocyanate
 1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate
 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Hazard statements

H226 Flammable liquid and vapour.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.
 EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.* **SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures****Description:** Mixture of the substances listed below with harmless additions.

Dangerous components:		
EC number: 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39-XXXX	isoparaffine hydrocarbon mixture Asp. Tox. 1, H304	20-40%
CAS: 53880-05-0 NLP: 500-125-5 Reg.nr.: 01-2119488734-24-XXXX	aliphatic polyisocyanate Skin Sens. 1, H317; STOT SE 3, H335	20-40%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.03.2019

Version number 6

Revision: 06.03.2019

Trade name **PRIMER PUR**

(Contd. of page 2)

CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119486773-24-XXXX	Solvent naphtha (petroleum), light arom. Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	≥10-<20%
CAS: 140921-24-0 ELINCS: 411-700-4 Index number: 616-079-00-5 Reg.nr.: 01-0000015906-63-XXXX	1,6-hexanediy-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate Skin Sens. 1, H317	5-10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	5-10%
CAS: 4098-71-9 EINECS: 223-861-6 Index number: 615-008-00-5	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Acute Tox. 1, H330; Resp. Sens. 1, H334; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<0.25%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally.

After inhalation

Take affected persons into the open air and position comfortably
Supply fresh air and call for doctor for safety reasons.
In case of unconsciousness bring patient into stable side position for transport.

After skin contact

If skin irritation continues, consult a doctor.
Wash immediately with water and soap and rinse thoroughly.

After eye contact Rinse opened eye for several minutes under running water.

After swallowing Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

In case of prolonged/repeated exposure or in high concentrations:

Headache

Dizziness

nausea

Unconsciousness

Inhalation may have an irritating effect on mucous membranes.

Danger Long-term or repeated exposure may cause inflammation of the skin (dermatitis).

4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

To avoid dermatitis (skin inflammation), use skin cream.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Foam

Water spray jet

Water mist

Dry extinguishing agents, carbon dioxide, sand or earth should only be used for small fires.

For safety reasons unsuitable extinguishing agents Water with a full water jet.

5.2 Special hazards arising from the substance or mixture

May be released in case of fire

Carbon monoxide (CO)

Nitrogen oxides (NOx)

Hydrogen cyanide (HCN)

(Traces)

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.03.2019

Version number 6

Revision: 06.03.2019

Trade name **PRIMER PUR**

(Contd. of page 3)

Formation of poisonous gases during heating or in fires.

Vapours are heavier than air and spread out over the ground. Ignition over greater distances is possible.

5.3 Advice for firefighters**Protective equipment:**

Wear self-contained breathing apparatus.

Wear full protective suit.

Put on breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

Put on breathing apparatus.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable containers.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of aerosols.

Information about protection against explosions and fires:

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep breathing equipment ready.

7.2 Conditions for safe storage, including any incompatibilities**Storage**

Requirements to be met by storerooms and containers: No special requirements.

Information on storage in a common storage facility:

Suitable material for containers and pipes: Light metals and their alloys.

Further information about storage conditions:

Store container in a well ventilated position.

Protect from humidity and keep away from water.

Keep container tightly closed.

7.3 Specific end use(s) No further relevant information available.

* SECTION 8: Exposure controls/personal protection

Additional information about design of technical systems: Use only in well-ventilated areas.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.03.2019

Version number 6

Revision: 06.03.2019

Trade name **PRIMER PUR**

(Contd. of page 4)

8.1 Control parameters

Components with limit values that require monitoring at the workplace:	
CAS: 108-65-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	
WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
Ingredients with biological limit values:	
CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	
BMGV	1 µmol creatinine/mol Medium: urine Sampling time: At the end of the period od exposure Parameter: isocyanate-derived diamine

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls**Personal protective equipment****General protective and hygienic measures**

Do not eat, drink or smoke while working.

Apply solvent-resistant skin protection preparation before beginning work.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Respiratory equipment:

Filter A (brown)

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

Protection of hands:

Solvent resistant gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

if there is a risk of splashes

Tightly sealed safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information****Appearance:**

Form: Fluid

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.03.2019

Version number 6

Revision: 06.03.2019

Trade name **PRIMER PUR**

(Contd. of page 5)

Colour:	Clear
Odour:	Solvent-like
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	51 °C (Setaflash)
Inflammability (solid, gaseous)	Not applicable.
Ignition temperature:	>200 °C
Decomposition temperature:	Not determined.
Self-inflammability:	Product is not self-igniting.
Explosive properties:	Product is not explosive. However, formation of dangerous explosive vapour/air mixtures is possible.
Explosive Limits:	
Lower:	0.6 Vol %
Upper:	10.8 Vol %
Vapour pressure at 20 °C:	1 hPa
Density at 20 °C:	0.98 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix
Distribution coefficient (n-octanol/water):	Not determined.
Viscosity:	
dynamic:	Not determined.
kinematic at 20 °C:	24 s (DIN 53211/4)
Solvent separation test	< 3 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

Avoid: heat, flames, sparks

10.3 Possibility of hazardous reactions Danger of bursting

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials:

Amines

Alcohols

10.6 Hazardous decomposition products: Isobutyraldehyde

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:		
isoparaffine hydrocarbon mixture		
Oral	LD50	>5,000 mg/kg (rat)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.03.2019

Version number 6

Revision: 06.03.2019

Trade name **PRIMER PUR**

(Contd. of page 6)

Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50/4 h	>20 mg/l (rat)

Skin corrosion/irritation: Dries skin out.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Sensitisation:

May cause an allergic skin reaction.

Experience with humans:

Frequent or longer lasting skin contact may degrease and dry out skin which may lead to skin irritation and inflammation (dermatitis).

Additional toxicological information:

Special characteristics/effects of isocyanates:

In case of over-exposure - especially when spraying isocyanate based varnishes without protective measures - there is a danger of a concentration-dependent, irritating effect on eyes, nose, throat, and respiratory tract. The delayed appearance of symptoms and the development of hypersensitivity (trouble breathing, cough, asthma) are possible. For hypersensitive persons, reactions may be triggered by very low isocyanate concentrations, also below the TLV value. In case of prolonged contact with skin, tanning and irritating effects are possible.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause respiratory irritation.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Harmful to fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

Recommendation

Liquid material remains are to be disposed of at collection facilities for old varnishes.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue	
08 05 01*	waste isocyanates

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 06.03.2019

Version number 6

Revision: 06.03.2019

Trade name **PRIMER PUR**

(Contd. of page 7)

SECTION 14: Transport information	
14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT
14.3 Transport hazard class(es) ADR	
	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user hazard identification number: EMS Number: Stowage Category	Warning: Flammable liquids. 30 F-E, S-E A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

* **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.03.2019

Version number 6

Revision: 06.03.2019

Trade name **PRIMER PUR**

(Contd. of page 8)

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3**National regulations****Other regulations, limitations and prohibition ordinances**

From the European Committee of the Associations for varnish, printing ink and artistry paint producers - CEPE - the following information is given for isocyanate based coating materials:

Ready-to-use coating materials that contain isocyanates may have an irritating effect on mucous membranes - especially on respiratory organs - and cause hypersensitivity reactions. There is a risk of sensitization if vapours or sprayed mist are inhaled. When handling isocyanate based coating materials, all measures for solvent based coating materials must be strictly observed. Sprayed mist and vapours especially should not be inhaled.

Persons with allergies or asthma who have a tendency for respiratory tract ailments should not be allowed to work with isocyanate based coating materials.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008 Calculation method**Department issuing data specification sheet:** Product Safety department / EHS**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 1: Acute toxicity – Category 1

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3