

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

Name of the product

PU AW

No. GBI F 045-2

Unique identification code of the product-type:

7630

Intended use/es:

**Sealant for facade for interior and exterior application -
EN 15651-1: F-EXT-INT**

Manufacturer:

**Remmers GmbH
Bernhard-Remmers-Str. 13
49624 Lönigen / Germany**

System/s of AVCP:

**System 3
System 3 for reaction to fire**

Harmonised standard:

EN 15651-1: 2012

Notified body/ies:

**Kiwa Polymer Institut GmbH
Quellenstraße 3
65439 Flörsheim-Wicker
Kennnummer 1119**

Declared performance/s:

Conditioning: Method A
 Substrate: Mortar M1
 Pre-treatment: Primer PUR

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 25 %		
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 100 %		
Durability	passed		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Remmers GmbH
 i. A. Stephanie Braak
 Head of laboratory sealants

Löningen, 01.11.2016

SBraak
 (signature)