

Technical Data Sheet
Art. No. 6752

Selectmix RMS

Fire-dried quartz sand mixture



Protect from
moisture!

Range of use

Selectmix 25 is used for the production of mortars and screed mixes in combination with Remmers epoxy resins.

Property profile

Special combination of fire-dried quartz sands.

Possible system products

- Epoxy BH 100
- Epoxy ESC 100
- Epoxy Quick 100

Delivery form, application rate, shelf-life

Packaging
25 kg bags

Characteristic data of the product

State:	solid
Colour:	white, yellowish
Density:	2,65 g/cm ³ (grain density)
Grain size:	ca. 0,1 – 3,0 mm

Application rate

Is determined by the type of application.

Shelf-life

Indefinite if stored dry.

Safety, ecology, disposal

Further information on safety when transporting, storing and handling as well as disposal and ecology is found in the latest Safety Data Sheet.

Emergency information

Mon.-Thurs. from 7:30 a.m. to 4:00 p.m., Fri. from 7:30 a.m. to 2:00 p.m.

Product Safety Department:
Tel.: +49(0)5432/83-138

After office hours:

Giftinformationszentrum-Nord
[Poison Information Centre North]
24 h hotline: +49 (0)551 -19240

The statements above are compiled from our field of production and according to the latest technological developments and application techniques.

Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid. With the publication of this Technical Information Sheet all previous editions are no longer valid.

6752 Selectmix RMS_11.16