

Technical Information Sheet Article No. 6747

Selectmix SBL

(Acolan SelectMix SBL)

Filler mixture with a special aggregate grading curve

Range of use

Selectmix SBL is a special filler for epoxy resins that are used for the production of highly filled flow covers or levelling layers.

Property profile

Because of the volume optimised composition of Select Mix SBL, the filler gives epoxy resin systems outstanding working properties:

- Neutral colour
- High wear resistance
- High degree of filling

Directions

Add the hardener to the basic compound and mix thoroughly with a slow speed mixer (max. 400 rpm). Pour the mixture into a separate container and mix again.

Insufficient mixing leads to the formation of blisters and causes soft, incompletely cured spots.

Notes

Please mind suitable protective equipment on the job (q.v. personal protective equipment).

The maximum degree of filling and the drying time depends on the epoxy resin used, the thickness of the layer and the conditions at the building site.

Characteristic data of the product

Appearance:	white, cream coloured
State:	solid
Density:	2.65 g/cm ³ (grain density)

When coating continuous surfaces, use only material with the same batch number; otherwise there may be slight differences in colour.

Tools, cleaning

Smoothing trowel, wiper, roller, brush. Mixing equipment, positive mixer. Clean tools, equipment and any splashed material with V 101 Thinner while fresh. Once the material has reacted, it can only be removed mechanically.

Further information are found in our tools programme.

Personal protective equipment

Suitable nitrile rubber gloves, protection goggles and splash guard.

Further information are found in our tools programme.

Packaging, shelf-life

Packaging:

15 kg paper sacks

Shelf-life:

At least 12 months stored dry and cool but frost-free in closed, original bags.

Safety, ecology, disposal

Further information on safety when transporting, storing and handling as well as disposal and ecology is found in the latest Safety Data Sheet and the brochure "Epoxy Resins in the Building Industry and the Environment" issued by Deutsche Bauchemie e.V. (2nd edition, as per 2009).

The statements above are compiled from our field of production and according to the latest technological developments and application techniques.

Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid. With the publication of this Technical Information Sheet all previous editions are no longer valid.

6747 Selectmix SBL_11.16.doc

Remmers India Pvt. Ltd.
Gurgaon
Tel.: +91 124 400 9131
Fax: +91 124 400 9134
www.remmers.in



Remmers (UK) Limited Crawley
United Kingdom
Tel: +44 (0) 1293 594 010
Fax: +44 (0) 1293 594 037
www.remmers.co.uk

Remmers (Far East) Pte. Ltd.
Singapore
Tel: +65 6 7410277
Fax: +65 6 7417158