



Technical Data Sheet Art. No. 7725

Smoothing Agent


Concentrate for subsequently smoothing sealing materials



Water-based

For use in-
doors and
outdoorsWorking
temperature

Spray application

Application rate-/
Depending on
useStore frost-free
and cool,
protected from
moisture in
closed containers

Shelf-life

Range of use

Smoothing Agent is an aid for subsequently smoothing fresh joint sealing materials.
Not recommended for use on acrylic sealants.

Property profile

Specially formulated concentrate for subsequently smoothing freshly produced elastic joints made with silicone, polyurethane or MS polymers.

Directions

Working conditions

Temperature of material, surroundings and substrate: +5 °C - +35 °C. Dilute Remmers Smoothing Agent with water to a concentration for use of 0.5 - 2.0% and apply to the fresh sealing compound using as primer.

Immediately afterwards, bring the sealing material in the desired form with a suitable tool. Excess Smoothing Agent should be quickly dried off to avoid traces from running, especially on glass.

Characteristic data of the product

Composition:	mixture of surface active agents, APEO-free
Active ingredient content:	approx. 35 %
Density (DIN 53217/2, 20 °C):	1.00 g/ml
pH value, 20 °C:	approx. 9

The values above represent typical characteristic data of the product and are not to be understood as product specifications.

Notes

Do not allow Smoothing Agent residue to dry since residue can lead to a loss of gloss on sealing materials or coatings. Before using, check compatibility with adjacent surfaces, e.g. coated wood, in a preliminary trial.

Possible system products

- MultiSil (7380)
- MultiSil NUW (7525)
- PU AW (7630)
- MS 150 (7505)
- Windowfix spatula (439401)

Application rate

According to needs

Tools, cleaning

Spray bottle or similar
Clean tools immediately after use with water and a detergent
Dispose of the remains from cleaning properly.

Packaging / Colour

Packaging

1 kg and 5 kg plastic containers

Shelf-life

At least 24 months in closed, original containers stored cool, dry and protected from frost.

Safety

Further information on safety when transporting, storing and handling as well as disposal and ecology is found in the latest Safety Data Sheet.

The statements above are compiled from our field of production and according to the latest technological developments and application techniques.

Since application and working are beyond our control, no liability of the producer can be derived from the contents of this information sheet. Any statements made beyond the contents of this information must be confirmed in writing by the producer.

In all cases, our general conditions of sale are valid. With the publication of this Technical Information Sheet all previous editions are no longer valid.

7725 Smoothing Agent_11.16



Remmers (UK) Limited Crawley
United Kingdom
Tel: +44 (0) 1293 594 010
Fax: +44 (0) 1293 594 037
www.remmers.co.uk