



Isover Renovation Roll Acoustic

Acoustic insulation for general renovation application

Isover Renovation Roll Acoustic is a glass mineral wool roll for multiple acoustic renovation applications. It will help to enhance acoustic performance when applied to partitions and separating walls and floors.

Supplied in 1200mm wide pre-perforated rolls for use in 400mm and 600mm applications.



Features and Benefits

Excellent Acoustic Properties

Helps to meet the requirements of Part E Acoustic Building Regulations (England & Wales) and Section 5 (Scotland)

Multiple Applications

Pre-perforated at 3x400mm and 2x600mm rolls to fit between standard 400mm and 600mm stud and joist spacing. Push fits between studs and joists with no need for additional fixings.

High Quality, Robust glass mineral wool

Easy to handle, cut and install with minimal on-site waste. Resilient to damage in storage, during transportation and on site.

Non-Combustible

Isover glass mineral wool is rated as Euroclass A1 – the best attainable.



Product Code	Thickness (mm)	Width (mm)	Length (mm)	Pack area (m ²)	Packs per pallet	Pallet area (m ²)
5200625518	50	1200	13000	15.60	24	374.4

Characteristic	Description
Thermal	<ul style="list-style-type: none"> All Isover products are manufactured under BS EN 13162:2012 and 13172:2012 for factory made mineral wool products. Isover Renovation Roll Acoustic has a declared thermal conductivity of 0.039 W/mK.
Fire	<ul style="list-style-type: none"> Euroclass A1 fire rating when classified to BS EN 13501-1.
Environmental	<ul style="list-style-type: none"> All Isover products are manufactured under Environmental Management System – ISO 14001:2004. Zero ODP (Ozone Depletion Potential), GWP < 5 (Global Warming Potential). The manufacturing process does not use or contain CFC's, HCFC's or other damaging gases.
BRE statement	<ul style="list-style-type: none"> Isover Renovation Roll Acoustic corresponds to the BRE Global Green Guide online generic specification 'Glass wool insulation - density 24 kg/m³' ref 81532002 which achieves a summary rating of A+ within Domestic, Health, Industrial, Commercial, Retail, Education. <p>NB: The density stated above is part of a generic BRE classification and does not reflect the exact specification of the product.</p>
Quality	<ul style="list-style-type: none"> All Isover products are manufactured under Quality Management Standard – ISO 9001:2008.
Building regulations	<ul style="list-style-type: none"> Helps to meet and exceed acoustic requirements detailed in Building Regulation Part E (England and Wales) and Section 5 (Scotland).
Recycled content	<ul style="list-style-type: none"> Isover glass mineral wool insulation is manufactured from up to 86% recycled glass that would otherwise go to landfill. This makes Isover one of the most environmentally sustainable insulation products on the market today.
Durability	<ul style="list-style-type: none"> Made from resilient glass fibre Will not accelerate corrosion in metallic building components. Will not sustain vermin, nor breed or promote fungi or bacteria.
Handling and storage	<p>Isover products are supplied fully palletised, offering the following benefits:</p> <ul style="list-style-type: none"> Weatherproof packaging for outside storage Reduced haulage costs Less handling therefore less damage Reduced storage space Packs remain clean and in good condition Faster loading, unloading and counting
Health & safety	<ul style="list-style-type: none"> A Material Safety Data Sheet can be obtained from the Isover website. Our REACH statement can be found at www.isover.co.uk
Certification	<ul style="list-style-type: none"> CE marked (1121-CPR-BA0053) to BS EN 13162:2012 and BS EN 13172:2012. Designation Code: MW EN13162 T1.

www.3pointplan.co.uk

www.isover.co.uk

Buildings Insulation - Technical Enquiries:
 Tel: 0115 945 1143
 Email: isover.enquiries@saint-gobain.com

Publish date: July 2014
Isover Document Reference: I-RRA-PDS-1402

Saint-Gobain Isover
 Gotham Road
 East Leake
 Loughborough
 Leicestershire
 LE12 6HX
 Tel: 0115 969 8010
 Email: isover@saint-gobain.com

Saint-Gobain Isover reserve the right to alter or amend product specification without notice. The information given in this publication is correct to the best of our knowledge at the time of publication. Whilst Saint-Gobain Isover will endeavor to ensure publications are up to date, it is the users responsibility to check with us that it is correct prior to use.