



# Isover Timber Party Wall Roll

## Thermal insulation for separating timber frame walls

Isover Timber Party Wall Roll is a glass mineral wool roll supplied in a 50mm, 75mm and 100mm thickness. The strong, resilient and flexible rolls are 1200mm and unsplit for fast coverage of large areas.

Isover Timber Party Wall Roll is designed for use in timber frame separating wall cavities to help deliver a zero U-value for party walls as defined in UK Building Regulations.



### Features and Benefits



#### Thermal Bypass Solutions

Meets the full-fill requirement to help deliver a zero U-value for party walls as defined in Building Regulations (Approved Document L1A, Table 3).



#### Recycled Content

Manufactured from up to 86% recycled post-consumer glass that would otherwise go to landfill.



#### Non-combustible

Isover glass mineral wool insulation has an A1 Euroclass fire rating – the best attainable.



#### Protected planet

Zero Ozone Depletion Potential (ODP) and Global Warming Potential of less than 5.

Product Code	Thickness (mm)	Cavity Thicknesses (mm)	Width (mm)	Length (mm)	Pack area (m <sup>2</sup> )	Packs per pallet	Density (k/m <sup>3</sup> )
5200624836	50	50	1200	12000	14.40	24	18
5200624787	75	51-75	1200	8000	9.60	24	18
5200624707	100	76-100	1200	6000	7.20	24	18

Characteristic	Description
Fire	Euroclass A1 fire rating when classified with BS EN 13501-1
Moisture	Resilient to moisture damage in storage, during transportation and on site during installation
Environmental	<ul style="list-style-type: none"> <li>• All Isover products are manufactured under Environmental Management System – ISO 14001:2004</li> <li>• Zero ODP (Ozone Depletion Potential), GWP &lt; 5 (Global Warming Potential)</li> <li>• The manufacturing process does not use or contain CFC's, HCFC's or other damaging gases</li> </ul>
BRE statement	Isover Timber Party Wall Roll corresponds to the BRE Global Green Guide online generic specification 'Glass wool insulation - density 24 kg/m <sup>3</sup> ' ref 815320002 which achieves a summary rating of A+ within Domestic, Health, Industrial, Commercial, Retail, Education
Quality	All Isover products are manufactured under Quality Management Standard – ISO 9001:2008
Building regulations	Meets the full-fill requirement to help deliver a zero U-value for party walls as defined in UK thermal building regulations
Recycled content	Isover glass mineral wool insulation is manufactured from up to 86% recycled glass that would otherwise go to landfill. This makes Isover one of the most environmentally sustainable insulation products on the market today.
Durability	<ul style="list-style-type: none"> <li>• Made from rot-proof non-hygroscopic materials</li> <li>• Will not accelerate corrosion with steel, copper or aluminium</li> <li>• Will not sustain vermin, nor breed or promote fungi or bacteria</li> </ul>
Handling and storage	<p>Isover products are supplied fully palletised, offering the following benefits:</p> <ul style="list-style-type: none"> <li>• Weatherproof packaging for outside storage</li> <li>• Reduced haulage costs</li> <li>• Less handling therefore less damage</li> <li>• Reduced storage space</li> <li>• Packs remain clean and in good condition</li> <li>• Faster loading, unloading and counting</li> </ul>
Health & safety	A Material Safety Data Sheet can be obtained from the Isover website

[www.3pointplan.co.uk](http://www.3pointplan.co.uk)

[www.isover.co.uk](http://www.isover.co.uk)

Buildings Insulation - Technical Enquiries:  
Tel: 0115 945 1143  
Email: [isover.enquiries@saint-gobain.com](mailto:isover.enquiries@saint-gobain.com)

Publish date: July 2014
Isover Document Reference: I-RDPW-PDS-1402

Saint-Gobain Isover  
Gotham Road  
East Leake  
Loughborough  
Leicestershire  
LE12 6HX  
Tel: 0115 969 8010  
Email: [isover@saint-gobain.com](mailto:isover@saint-gobain.com)

Saint-Gobain Isover reserve the right to alter or amend product specification without notice. The information given in this publication is correct to the best of our knowledge at the time of publication. Whilst Saint-Gobain Isover will endeavor to ensure publications are up to date, it is the users responsibility to check with us that it is correct prior to use.