



ALBAN PARK TEL. 01727 837271
 ST. ALBANS. HERTS. FAX. 01727 844053
 AL4 0JJ.

**DATA
 SHEET
 NUMBER**

DS-545

SERIES 45 SINGLE AND DOUBLE CASEMENT UNITS

Operating Instructions:

Single Casements: The unit is fitted with multi point locking operated by handle or “T” key. When the handle is turned to the horizontal position it releases the catches allowing the vent to ease forward. The vent is supported on a seating block and this will provide a small amount of resistance to opening. A sliding arm limits opening to approximately 90°. Avoid fast movement since this could damage the stay. The handle should not be turned when the window is in the open position since the locking catches could be damaged if an attempt is then made to close the window.

Double Casements: The main leaf is operated in the same way as the single casement. The ‘slave’ leaf has a small retention bolt which engages in the bottom frame. This bolt must be released to allow the vent to swing open and, to ensure a proper seal, should be re-engaged before closing the main leaf.

Maintenance:

Lubrication: The handle gear is sealed with lubricant before assembly, but hinges and locking points should receive occasional lubrication with a silicone spray.

Locking points: These operate on a cam action. If there is too much resistance to opening or closing the window the cams can be adjusted laterally using an Allen key.

Re-glazing: Re-glazing is a specialist operation, refer to Selectaglaze.

DRAWN	DATE	ISSUE	AA	AB				
S. THOMPSON	31-08-07	C.N.	07/040	15-014				
DESCRIPTION	SERIES 45 – SIDE HUNG CASEMENT UNIT							
This document is the property of Selectaglaze Ltd., and is issued on the express terms that it is to be treated as private and confidential and is not to be copied or communicated to any person. All patents, manufacturing and design rights are reserved by Selectaglaze Ltd.			SHEET 1 OF 1 SHEETS		CAD FILE NAME		DS-545-AB.doc	
			DATA SHEET NUMBER		DS-545		ISSUE	AB