

# Decothane Accelerator

## Catalyst

### Product Description

Decothane Accelerator is designed to increase the cure rate of Decothane products to facilitate a faster application and reduce downtime in areas where a rapid return to service is required.

### Uses

An accelerator to shorten the curing time of Decothane Base Coat, Decothane Top Coat, Decothane Root Resistant Base Coat, Decothane Root Resistant Top Coat, Decothane Root Resistant Detail Coat, Decothane Balcons and Decoquick.

### Characteristics / Advantages

- Reduces downtime in areas where a fast return to service is required
- Avoids delays due to lower temperatures

## Product Data

### Form

#### Appearance

Clear, low viscosity liquid

#### Packaging

Available in 60ml (to be used in 5 Litre packs) and 180ml (to be used in 15 Litre packs)

### Storage

#### Storage Conditions / Shelf Life

9 months from date of production if stored properly in original, unopened and undamaged sealed pack. Expiry date on pack.

## Technical Data

#### Chemical Base

Catalyst in hydrocarbon solvent

#### Density

1.02 kg/L

## System Information

## Application Conditions and Limitations

#### Substrate and Ambient Temperature

Refer to the specific product technical datasheet



---

**Relative Air Humidity**      Refer to the specific product technical datasheet

---

**Dew Point**      Refer to the specific product technical datasheet

Beware of condensation. Surface temperature during application must be at least +3°C above dew point.

---

## Application Instructions

---

**Application Method**      Mixing Level: 1% by weight.

The material should be added to the specific Decothane product on site at the time of application and mixed manually or mechanically at slow speed to prevent aeration. Mix with electric drill and paddle.

---

**Application Tools**      Refer to the specific product technical datasheet

---

**Cleaning of Tools**      Refer to the specific product technical datasheet

---

**Waiting Time / Overcoating**      Refer to the specific product technical datasheet for the accelerated drying times.

---

## Curing Details

---

**Approximate Curing Times**      Once the Decothane Accelerator is added, the specific Decothane product must be used immediately. The product has a working life of 1 hour. Ensure suitable PPE is worn when handling, mixing and applying the product.

---

## Notes on Application

---

**Health and Safety Information**      For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

---

## General Information

---

**Specification Assistance**      NBS is the industry standard specification system, which allows architects, specifiers and engineers to insert clauses into specifications by manufacturer and product, making the process quicker and more efficient. We are members of NBS Plus and therefore detailed up-to-date product information is readily available to create accurate specifications.

## Product Data Sheet

Edition 12.2011  
Identification no.  
020945074900000005  
Version no. 01

### Disclaimer

The information, and, in particular, the recommendations relating to the application and end- use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Contact Details

For further information please contact:

Sika Liquid Plastics  
Sika House  
Miller Street  
Preston  
PR1 1EA

Enquiry Line: 01772 259781

Fax: +44 (0)1772 255670  
e-mail: [liquidplastics@uk.sika.com](mailto:liquidplastics@uk.sika.com)

# Roofing



Registered office: Sika Ltd, Watchmead, Welwyn Garden City, Hertfordshire, AL7 1BQ  
Registered in England: 226822

