



EN 13165

12

0751 and 1104

DECLARATION OF PERFORMANCE

SarnaTherm G

02	09	45	05	125	0	005001	1087
----	----	----	----	-----	---	--------	------

1. Product Type: Unique identification code of the product-type:	SarnaTherm G
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	G (Batch nr see packaging)
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Thermal insulation for buildings according to EN 13165 Factory made rigid polyurethane foam (PU) products.
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	SarnaTherm G Sika Limited Bankside 300 Peachman Way Broadland Business Park Norwich NR7 0WF
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not relevant (see 4)
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 3
7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	EN 13165:2012 Notified testing laboratory No. 0751 and 1104 carried out determination of the product type on the basis of type testing (based on sampling carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product under system AVCP 3

Declaration of Performance



8. Notified body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	Not relevant (refer to item 7)
--	---------------------------------------

9. Declared performance

Essential Characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	RtF E	EN 13501-1	EN 13165: 2012
Thermal resistance ((m ² .K)/W)	d _N 30mm 1.15 d _N 40mm 1.50 d _N 50mm 1.90 d _N 60mm 2.30 d _N 70mm 2.65 d _N 80mm 3.20 d _N 90mm 3.60 d _N 100mm 4.00 d _N 110mm 4.40 d _N 120mm 5.00 d _N 130mm 5.40	EN 12667 EN 12939	
Thermal conductivity λ _D (W/(m.K))	d < 80mm; 0.026 80mm ≤ d < 119mm; 0.025 d ≥ 120mm; 0.024		
Thickness	d _N < 50mm T2; ± 2mm d _N 50-75mm T2; ± 3mm d _N > 75mm T2; + 5, - 3mm	EN 823	
Compressive Strength	d 30 to 160mm (kPa) CS(10/Y)150	EN 826	
Tensile Strength	Perpendicular to faces (kPa) TR80	EN 1607	
Dimensional stability under specified temperature and humidity conditions	48 h, 70 °C, 90 % R.H. DS(70,90)3 48 h, -20 °C DS(-20,-)1	EN 1604	
Deformation under specified compressive load and temperature conditions	40 kPa, 70°C, 168h DLT(2)5	EN 1605	



10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



R&D Manager



Technical Manager

04, 2013

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet (MSDS) containing physical, ecological, toxicological and other safety related data.

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire
AL7 1BQ
United Kingdom
Phone +44 1707 394444
Telefax +44 1707 329129
www.sika.co.uk
email: sales@uk.sika.com



Certificate No. EMS 4308



Certificate No. FM 12504