

Sarnavap Tape F

Butyl rubber adhesive tape

Product Description

Sarnavap Tape F with double-sided adhesion, is a butyl rubber sealing tape with overstretching prevention.

Uses

- Sarnavap Tape F is used for taping laps in Sarnavap vapour control layers (polyethylene) based material and for attaching Sarnavap VCL to smooth surfaces.
- Sarnavap Tape F can only be used exclusively at airtight level.

Characteristics / Advantages

- Polypropylene liner with finger-lift
- Adhesive mass with overstretching prevention
- Solvent-free
- Very high durability

Product Data

Form

Appearance/Design Flat section, double side adhesion

Colour Anthracite

Packaging Packing unit: see price list

Storage

Storage Conditions Store rolls protected from direct sunlight, rain and snow at temperatures between +5 °C to +25 °C.

Shelf-Life At least 24 months from date of production if stored properly. Expiry date is on label.



Technical Data

Material Basis	Butyl rubber
Length	40.00 m (- 5 cm / + 20 cm)
Width	15 mm (\pm 1.0 mm)
Thickness	1.0 mm (- 0 mm / + 0.2 mm)
Density	1.2 g/cm ³ (+20 °C)

System Information

System Structure	Compatible with : - Sarnavap PE vapour control layer
-------------------------	---

Application Details

Substrate Quality	The contact surfaces must be sturdy, dry, clean and free from dust, grease and other materials that impair adhesion.
--------------------------	--

Application Conditions / Limits

Temperature	The use of Sarnavap Tape F is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.
Compatibility	Not compatible in direct contact with PVC, tar, asphalt, hot bitumen, wood preservatives with surfactants and substances containing oil, solvents or wetting agents.
Resistance	Not applicable for permanent exposure to UV irradiation

Installation Instructions

Installation Method	According to the valid installation instructions for Sarnafil® flat roof systems. Adjoining sheets must overlap 80 mm.
Notes on Installation/ Limits	Installation works shall be performed only by Registered Sarnafil® Contractors. Temperature limits for the installation of the Sarnavap Tape F: For bonded seams and detail versions mind. +5 °C / max. +40 °C

Roofing

Value Base	All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.
Ecology, Health and Safety Information	The product does not fall within the EC-regulation of hazardous goods. As a result, a material safety data sheet following EC-Guideline 91/155 EWG is not needed to bring the product to the market, transport or use it. The product does not damage the environment when used as specified.
Protective Measures	Regulatory safety requirements must be observed.
Transportation Class	The product is not classified as hazardous good for transport.
Disposal	The material is recyclable. Disposal must be according to regulatory requirements.

All data in our product information are based on our current knowledge and experience. They do not release users from careful testing of the application and strict observation of the relevant processing regulations because of the wide range of possible influences during the application and use of our products. Legally valid assurances of specific characteristics or suitability for special purposes of application other than those provided in our documentation for the specific product cannot be inferred from our information. Any protective rights or existing laws and provisions must be followed by the recipient or processor of our products at their own responsibility. Moreover our general terms and conditions of sale and guarantee are valid.



Sika Ltd, Bankside 300, Peachman Way, Broadland Business Park,
Norwich, NR7 0WF.

Tel: 01603 709360 Fax: 01603 433436 Email: sarnafilroofing@uk.sika.com

Registered Office: Sika Ltd, Watchmead, Welwyn Garden City, Hertfordshire, AL7 1BQ
Registered in England: 226822



Sarnafil®