

MediaStar 4K UHD IPTV and Media Player (782-AV)



The 782-AV is a powerful, purpose designed and ultra-reliable solid state media player, a full 4K UHD multizone digital signage platform and a networked 'Live' stream IPTV decoder. With HTML5 support, on board memory and local input capability it is ideal for any deployment

Key Features

- Supports SD, HD and UHD multizone screen formats
- Decodes HEVC, H264, VP8, MPEG2 video standards
- Renders HTML5, JPEGS, PNG, GIFs
- DVB TeleText / CC subtitles
DolbyDigital+ Multilanguage
- Zones can contain Video, RSS text, tickers, realtime clocks
- AES 128 decryption capability
- CEC & RS-232 screen control, IR blaster functionality
- IP to RS-232 pass through, external contact closures (6)
- Low power consumption - PoE or DC adaptor options

A 782-AV will support a variety of video formats that can be displayed full screen or scaled to any size using the built in hardware decoding engine. A single UHD 4K resolution HEVC or H264 video can be played out, or multiple 1080i H264/MPEG2 videos can be shown. The video can be stored either locally in on-board flash, accessed from a remote RTSP video server or played from 'Live' multicast network streams.

Using HTML5, the full UHD 4K screen resolution can be a configured webpage to simultaneously show different forms of media in different dynamic zones, each of which can contain video playback, RSS text feeds, smooth scrolling tickers, real-time clocks and HTML web pages as well as support for graphics widgets.

The 782-AV also has a front panel HDMI video and Line/Mic audio input, enabling local AV input sources to be displayed at full screen or within a selected zone as part of a composite image.

This functionality can be used for creating multi-zone signage streams, lecture capture or for broadcasting live presentations.

The 782-AV can operate reliably on its own in "Standalone" mode or networked under the control of the MediaStar Media Manager software suite (Part 462) enabling a system administrator to configure an extensive range of time based and user selected media layout controls.

Infrared, RS-232, HDMI CEC and USB connectivity enable local operation such as display control; keyboard and mouse interaction; IP command pass through for 3rd party control systems and external alarm audio mute. The unit will also email proof of play reports and send SNMP traps if required.

An IR blaster output is available as well as 6 external contact closures for external control functions.

Available with multiple memory options and with its maintenance free operation, small physical size, low power consumption and software future proofing, the 782-AV is ideally suited for both large scale distributed applications or simple single screen deployments. Please see model options below.

Model options: 782-AV-8, 782-AV-8-POE, 782-AV-32, 782-AV-32-POE, 782-AV-64, 782-AV-64-POE, 782-AV-128, 782-AV-128-POE

Head Office
Cabletime LTD, 65 Greenham Road, Newbury, United Kingdom
RG14 7HX
T:+44 1635 35111 E:sales@cabletime.com www.cabletime.com

USA Office
Cabletime USA T:973 770 8070 E:usa@cabletime.com

Asia Office
Cabletime ASIA T:+852 3101 2650 E:asia@cabletime.com

MEDIASTAR 
BY CABLETIME

Specifications

COMMUNICATIONS AND CONTROL

NETWORK

Ethernet 10/100/1000 Base T. RJ-45 802.3 modular jack with integrated LEDs

Static or DHCP IP Address

DSCP stream tagging for QoS.

MODE OF OPERATION

Standalone or controlled by the MediaStar Media Manager Software.

IP SETUP AND CONTROL

Full configuration via on-board browser with remote status monitoring information

Initial IP address configuration via DHCP or local IR remote control

IP/RS232 control protocol to operate with 3rd party touch panel controllers

IR CONTROL

Channel, volume and setup control via MediaStar Remote Control Unit.

Control through on-board IR receiver or optional IR extender module.

IR Pass Back - IR signals can be routed back via the IP network to IR controlled devices at the headend.

RS-232

Rx, Tx, CTS, RTS up to 115,200 Baud Configured for SIPI external configuration/control or IP to RS-232 bidirectional pass through for external device control.

SOFTWARE UPDATES

Fully upgradable ONLY with protected Cabletime software from MediaStar Media Manager HTTP server or by front panel USB Key

VIDEO

HDMI 1.4b - DIGITAL OUTPUT

CEC Support for screen control

SD 480i, 480p, 576i, 576p

HD 720p (50/60), 1080i (50/60), 1080p (50/60)

UHD 2160p (25/30)

PHONO - ANALOGUE OUTPUT

(YPbPr) HD 720p (50/60), 1080i (50/60), 1080p (50/60)

(CVBS) - SD - NTSC, PAL

HDMI - LOCAL DIGITAL INPUT

SD 480i, 480p, 576i, 576p

HD 720p (50/60), 1080i (50/60) 1080p (50/60)

AUDIO

AUDIO DECODING

MPEG-1/2 audio layers I, II

HE-AAC LC

Dolby Digital+

AUDIO OUT - CONNECTORS

HDMI - PCM Digital multichannel or stereo audio

3.5mm 4 pole Jack - Analogue audio downmixed to stereo, also microphone input

LOCAL AUDIO INPUTS

HDMI - PCM Digital stereo audio

3.5mm 4 pole Jack - Analogue stereo audio, selectable microphone or line input

Line input - 2.2V pk-pk into 10k Ohms

OTHER CONNECTIONS

USB

1 x USB2 port, 1 x USB3 port

For software updates and connection of external storage devices

Supports keyboard/mouse and other peripherals for interaction with the unit.

ALARM INPUT

3.5mm 4 pole jack socket, 2 x Contacts (Normally open or normally closed - user selectable)

Type D 9 way connector, 4 x Contacts (Normally open or normally closed - user selectable)

OTHER INFORMATION

DIMENSIONS:

18.0cm x 12.4 cm x 2.8cm / 7 1/4" x 4 7/8" x 1 1/8"

WEIGHT:

0.42Kg/0.9lb

OPERATING TEMPERATURE:

0 - 40°C; 32 - 104°F

OPERATING PLATFORM:

Linux 3.10 Kernel

POWER SUPPLY:

AC mains adaptor, LPS 100-240VAC, 47-63Hz Output: +5VDC (+/- 5%), 3.0 Amps, with a DC jack plug (centre positive voltage, 5.5/2.1mm diameter)

Power over Ethernet (PoE models only) 802.3af class 0 device (13 W max), 802.3at class 4 device (25 W max)

POWER DISSIPATION:

12W max

APPROVALS:

FCC Part 15 class A, CE, CB

ON-BOARD BROWSER:

WebKit

What's in the box?

782-AV Unit; Quick Start Guide; HDMI Cable (1.0m)
DC Power adaptor (With Non PoE versions only)

Upgrade Options

782-AV-XX - Other memory options are available, please contact your supplier for further information.

About Smart Presentations Limited

WHAT WE DO

Smart Presentations Limited is an innovative technology systems integrator. We help organisations expand the potential of what groups of people working together can achieve.

Our interactive technology solutions deliver tools and working processes that drive business productivity and bring greater success.

Our mission is to be the preferred choice for organisations by virtue of our reputation and the quality of our services: 'Right First Time'.

Our reputation for delivering what we say we will on the day of completion is the foundation of our long-term success. This positive experience has made us our clients' preferred choice – and brings us lots of referred business.

'Right First Time' means all client projects are delivered:

- Fully operational
- On time
- Snag free
- All project documentation on completion

OUR APPROACH

Our consultative approach allows every client to benefit from a comprehensive 'one-stop-shop' service for AV systems integration:

- Consultancy
- Project Management
- Installation
- Training
- Maintenance
- Asset Value Plan (lease finance)
- Rental

SAY HELLO....

Let us help you drive productivity with innovative technology for your business that will make your presentations and meetings go further.

01296 642000

info@presentations.co.uk

www.presentations.co.uk

