



OAK CHEVRON ETNA

Imagine oak that has had the full force of the elements weathering its surface: fire, natural chemicals and coloured oils carve out a deep texture and enhance the grain to create this stunning white-washed floor. Parquet has been installed as eye-catching flooring options for centuries. We have given this chevron pattern a contemporary twist to create an elegant, beautifully textured floor. Available in 45 and 60° chevron, and also comes in herringbone patterns and various board widths.

Click [HERE](#) for prices and sizes

SIZE AND FINISH

| | |
|-------------------|--------------------------------------|
| THICKNESS | 20mm or 21mm |
| WIDTH | 65mm, 85mm, 145mm or 185mm |
| LENGTH | 325mm, 425mm, 580mm, 725mm or 925mm |
| GRADE | Select/Natural or Natural/Rustic mix |
| SURFACE TEXTURE | Heavily textured |
| SURFACE TREATMENT | Hard-wax oiled |

TECHNICAL SPECIFICATIONS

| | |
|------------------------|--|
| SPECIES | European Oak (Quercus Robur) |
| CERTIFICATION | Solid: FSC 100% |
| APPLICATION | Engineered: FSC mix 70% |
| CONSTRUCTION | Commercial and residential indoor use Solid: 20mm solid oak |
| BEVEL | Engineered: 6mm top-layer oak Micro, standard or hand-scraped bevel |
| INSTALLATION TECHNIQUE | Nailing or glue-bonding |
| SUITABLE FOR UFH | Yes, if engineered |
| FIRE CLASSIFICATION | Solid: EN 13501: Cfl-S1 Engineered: EN 13501: Dfl-S1 |
| THERMAL CONDUCTIVITY | Solid: 0.153 λ W/mK Engineered: 0.119-0.157 λ W/mK |
| HARDNESS | 4,982 N (Janka) |

Timber floors are easy to care for. Please see our Library pages for care sheets of the various floor finishes, or call us for further information.

Timber is a living material. A wooden floor, although no longer growing as part of a tree, is still very much part of its environment. As such, it responds to the light, temperature, humidity and wear to which it is exposed. As a general rule, a proper wooden floor takes four seasons to settle in. Over this time, it is normal to see some movement in the boards owing to changes in temperature and humidity.

As the floor ages the colour of the wood will mellow and change. This is a natural process that occurs as the surface of the wood is exposed to oxygen in the air and to ultraviolet light from the sun. Painted surfaces, upholstery, furniture and rugs all undergo this same process over time.

After a number of years you may wish to have the floor surface sanded down and re-finished. You could then choose to re-oil the floor or have it stained first or even re-finished in lacquer.