



## OAK COLOUR COLLECTION WHITE

Add a splash of paint colour to your oak floors! With vivid colours from across the spectrum, this vibrant collection is a good choice for residential and commercial projects alike.

### SIZE AND FINISH

THICKNESS	20mm
WIDTH	140mm
LENGTH	Random
GRADE	Natural/Rustic mix
SURFACE TEXTURE	Hand-scraped and reclaimed look
SURFACE TREATMENT	Painted

### TECHNICAL SPECIFICATIONS

SPECIES	European Oak (Quercus Robur)
CERTIFICATION	FSC mix 70%
APPLICATION	Commercial and residential indoor use
CONSTRUCTION	Engineered 6mm top-layer oak
BEVEL	Hand-scraped bevel
INSTALLATION TECHNIQUE	Nailing, glue-bonding and floating
SUITABLE FOR UFH	Yes, if engineered
FIRE CLASSIFICATION	EN 13501: Dfl-S1
THERMAL CONDUCTIVITY	0.119-0.157 $\lambda$ W/mK
HARDNESS	4,982 N (Janka)

Timber floors are easy to care for. Please see our Library pages for care sheets of the various floor finishes, or call us for further information.

Timber is a living material. A wooden floor, although no longer growing as part of a tree, is still very much part of its environment. As such, it responds to the light, temperature, humidity and wear to which it is exposed. As a general rule, a proper wooden floor takes four seasons to settle in. Over this time, it is normal to see some movement in the boards owing to changes in temperature and humidity.

As the floor ages the colour of the wood will mellow and change. This is a natural process that occurs as the surface of the wood is exposed to oxygen in the air and to ultraviolet light from the sun. Painted surfaces, upholstery, furniture and rugs all undergo this same process over time.

After a number of years you may wish to have the floor surface sanded down and re-finished. You could then choose to re-oil the floor or have it stained first or even re-finished in lacquer.