



## OAK HERRINGBONE DALTON

Parquet has been installed as an eye-catching flooring option for centuries. We have given this herringbone pattern a contemporary twist to create a lively brown modern floor. By planing rather than sanding the surface, we tear open the Landmark oak grain. The application of smoking and coloured oils further accentuates the visual appeal. These are floors of distinction, also available in wide boards and other pattern.

Click [HERE](#) for prices and sizes.

### SIZE AND FINISH

THICKNESS	Engineered: 15mm or 20mm Solid overlay: 6mm
WIDTH	65mm, 70mm, 85mm, 90mm, 145mm or 185mm
LENGTH	325mm, 350mm, 425mm, 450mm, 580mm, 725mm or 925mm
GRADE	Select/Rustic or Rustic/Natural mix
SURFACE TEXTURE	Planed, also available in reclaimed look
SURFACE TREATMENT	Hard-wax oiled

### TECHNICAL SPECIFICATIONS

SPECIES	European Oak (Quercus Robur)
CERTIFICATION	Engineered: FSC mix 70% Solid overlay: Not certified
APPLIICATION	Commercial and residential indoor use
CONSTRUCTION	Overlay: 6mm solid oak Engineered: 4mm or 6mm top-layer oak
BEVEL	Micro, standard or hand-scraped bevel
INSTALLATION TECHNIQUE	Nailing or glue-bonding
SUITABLE FOR UFH	Yes, if engineered
FIRE CLASSIFICATION	Solid: EN 13501: Cfl-S1 Engineered: EN 13501: Dfl-S1
THERMAL CONDUCTIVITY	Solid: 0.153 $\lambda$ W/mK Engineered: 0.119-0.157 $\lambda$ W/mK
HARDNESS	4,982 N (Janka)

Timber floors are easy to care for. Please see our Library pages for care sheets of the various floor finishes, or call us for further information.

Timber is a living material. A wooden floor, although no longer growing as part of a tree, is still very much part of its environment. As such, it responds to the light, temperature, humidity and wear to which it is exposed. As a general rule, a proper wooden floor takes four seasons to settle in. Over this time, it is normal to see some movement in the boards owing to changes in temperature and humidity.

As the floor ages the colour of the wood will mellow and change. This is a natural process that occurs as the surface of the wood is exposed to oxygen in the air and to ultraviolet light from the sun. Painted surfaces, upholstery, furniture and rugs all undergo this same process over time.

After a number of years you may wish to have the floor surface sanded down and re-finished. You could then choose to re-oil the floor or have it stained first or even re-finished in lacquer.