



OAK SHABBY CHIC GREY

Shabby chic equals Boho style. These painted and distressed oak floors have a well-worn surface. Choose from a carefully curated colour selection from muted to drab. This quirky grey floor adds charm to any room and also comes in herringbone and chevron patterns.

SIZE AND FINISH

THICKNESS	15mm or 20mm
WIDTH	185mm-245mm
LENGTH	Random
GRADE	Rustic
SURFACE TEXTURE	Distressed
SURFACE TREATMENT	Painted

TECHNICAL SPECIFICATIONS

SPECIES	Oak (Quercus spp)
APPLICATION	Commercial and residential indoor use
CONSTRUCTION	Solid: 15mm or 20mm solid oak Engineered: 3.5mm or 5.5mm oak top-layer
BEVEL	Hand-scraped bevel
INSTALLATION TECHNIQUE	Nailing, glue-bonding and floating
SUITABLE FOR UFH	Yes, if engineered
FIRE CLASSIFICATION	Solid: EN 13501: Cfi-S1 Engineered: EN 13501: Dfi-S1
THERMAL CONDUCTIVITY	Solid: 0.153 λ W/mK Engineered: 0.119-0.157 λ W/mK
HARDNESS	1,120 lbf (Janka)

Timber floors are easy to care for. Please see our Library pages for care sheets of the various floor finishes, or call us for further information.

Timber is a living material. A wooden floor, although no longer growing as part of a tree, is still very much part of its environment. As such, it responds to the light, temperature, humidity and wear to which it is exposed. As a general rule, a proper wooden floor takes four seasons to settle in. Over this time, it is normal to see some movement in the boards owing to changes in temperature and humidity.

As the floor ages the colour of the wood will mellow and change. This is a natural process that occurs as the surface of the wood is exposed to oxygen in the air and to ultraviolet light from the sun. Painted surfaces, upholstery, furniture and rugs all undergo this same process over time.

After a number of years you may wish to have the floor surface sanded down and re-finished. You could then choose to re-oil the floor or have it stained first or even re-finished in lacquer.