



## OAK URBAN CASSIS

Which city are you? Covering the whole colour spectrum of oak from cool grey-white to dark browns, those who appreciate clean, simple colours will find something to love in our Urban collection. This quiet pale floor brings scandi cool to any setting and is available in boards and parquet.

Click [HERE](#) for prices and sizes

### SIZE AND FINISH

THICKNESS	Tryplank: 21mm, Solid Overlay 9mm Engineered: 21mm, 14mm or 13mm
WIDTH	Boards: 182mm-190mm-220mm-240mm Parquet: 70mm, 90mm, 120mm, 140mm or 182mm
LENGTH	Fixed or random
GRADE	Select, Natural or Select/Natural/Rustic mix
SURFACE TEXTURE	Sanded/smooth, also available in brushed or reclaimed look
SURFACE TREATMENT	Hard-wax oiled

### TECHNICAL SPECIFICATIONS

SPECIES	European Oak (Quercus Robur)
CERTIFICATION	Solid 20mm and 9mm: 100% PEFC certified Engineered 21mm: FSC 100% Engineered 14mm: FSC mix credit Engineered 13mm: 100% PEFC certified
APPLICATION	Commercial and residential indoor use
CONSTRUCTION	Solid: 20mm or 9mm solid oak Engineered: 6mm, 4mm or 3.5mm top-layer oak
BEVEL	Micro, standard or hand-scraped bevel
INSTALLATION TECHNIQUE	Nailing, glue-bonding and floating
SUITABLE FOR UFH	Yes, if engineered
FIRE CLASSIFICATION	Solid: EN 13501: Cfl-S1 Engineered: EN 13501: Dfl-S1
THERMAL CONDUCTIVITY	Solid: 0.15 $\lambda$ W/mK Engineered: 0.12 $\lambda$ W/mK
HARDNESS	4,982 N (Janka)

Timber floors are easy to care for. Please see our Library pages for care sheets of the various floor finishes, or call us for further information.

Timber is a living material. A wooden floor, although no longer growing as part of a tree, is still very much part of its environment. As such, it responds to the light, temperature, humidity and wear to which it is exposed. As a general rule, a proper wooden floor takes four seasons to settle in. Over this time, it is normal to see some movement in the boards owing to changes in temperature and humidity.

As the floor ages the colour of the wood will mellow and change. This is a natural process that occurs as the surface of the wood is exposed to oxygen in the air and to ultraviolet light from the sun. Painted surfaces, upholstery, furniture and rugs all undergo this same process over time.

After a number of years you may wish to have the floor surface sanded down and re-finished. You could then choose to re-oil the floor or have it stained first or even re-finished in lacquer.