

BOARDWALK
7 SIZES • 8 COLOURS • 2 FINISHES






3web41573




3web41568




3web41569




3web41567




3web41572



3web41571



3web41574




3web41570





	110x900 10.5mm	150x900 10.5mm	150x1200 10.5mm	200x1200 10.5mm	225x900 10.5mm	450x900 10.5mm	600x1200 10.5mm
3web41573	●	●	● ○*	● ○*	●	●	● ○*
3web41568	●	●	● ○*	● ○*	●	●	● ○*
3web41569	● ○	●	● ○*	● ○*	●	●	● ○*
3web41567	●	●	● ○*	● ○*	●	●	● ○*
3web41572	● ○	●	● ○*	● ○*	●	●	● ○*
3web41571	●	●	● ○*	● ○*	●	●	● ○*
3web41574	● ○	●	● ○*	● ○*	●	●	● ○*
3web41570	● ○	●	● ○*	● ○*	●	●	● ○*




● Matt R10 (B) ○ Matt Outdoor R11 (B+C) * Minimum order applies

Square and round top plinths and step treads are also available. For more information contact our sales team.



	Dimensions and Surface Quality	ISO 10545-2 Conforms
	Water Absorption	ISO 10545-3 < 0.1%
	Flexural Strength	ISO 10545-4 50-60 N/mm ²
	Deep Abrasion Resistance	ISO 10545-6 No Rating

	Linear Thermal Expansion	ISO 10545-8 6x10 ⁻⁶ °C
	Thermal Shock Resistance	ISO 10545-9 No Rating
	Moisture Expansion	ISO 10545-10 No Rating
	Frost Resistance	ISO 10545-12 Conforms

	Chemical Resistance	ISO 10545-13 Conforms
	Stain Resistance	ISO 10545-14 Conforms
	Slip Resistance	DIN 51130 - 51097 Matt R10 (B) Matt Outdoor R11 (B+C)

On request tiles can be tested to PTV BS7976-2. HSE surface roughness and NCS Colour values are also available.

