

# SONA® WTSL-SN-1

Battery powered alarm control unit for Wi-Safe 2 enabled alarms and devices

## Wi-Safe® 2

### Dimensions:

Height: 90mm

Width: 90mm

Depth: 22.5mm

Weight: 142g



## Features

- A remote interface between up to 50 products (smoke / heat / CO) within the Wi-Safe 2 product range.
- **Test button** - test all interlinked alarms from one centralised location.
- **Silence button** - silence all interlinked smoke and heat alarms.
- **Locate button** - silence all interlinked alarms except the initiating alarms.
- Memory function - if one of the alarm indicators is flashing every 10 seconds this indicates that a smoke, heat or CO alarm has previously activated.
- Fire and CO alarm identification.
- 10 year sealed for life battery back-up.

## Technical Specification

<b>Battery</b>	10 year sealed alkaline batteries
<b>Technology</b>	Wi-Safe 2
<b>Installation positions</b>	Wall / Portable
<b>Operating temperature</b>	+4°C to +38°C
<b>Operating humidity</b>	Up to 90% RH non-condensing
<b>Storage temperature</b>	-20°C to +60°C
<b>Storage humidity</b>	Up to 93% RH non-condensing
<b>Plastic material</b>	UL94 V0 flame retardant
<b>Warranty</b>	5 years
<b>Master pack quantity</b>	4
<b>Certified to</b>	BS EN 60065: 2002
<b>Independently tested to</b>	IEC 600: 2001 (seventh edition)+ A11: 2008+ A12: 2011
<b>Operating frequency</b>	868 MHz
<b>Maximum number of connected units</b>	50 wireless units
<b>Wireless Range</b>	35m (over 200m in clear air)



Wi-Safe 2 module contained within WTSL-SN-1 independently tested to RF standard ETSI EN 300 220-2 V2.3.2 (2010-02) by TRaC Global Ltd EN300489-1 &-3 / EN300220-2 - Radio

FOR FURTHER INFORMATION OR SALES ENQUIRIES:

Tel +44 (0) 2477 717 700 Email [sales@sonasafety.com](mailto:sales@sonasafety.com) Website [sonasafety.com](http://sonasafety.com)

