



Data Sheet No:  
TDS 262  
Version 3

## TECHNICAL DATA SHEET

### Description

Sovereign PLASPRIME® is a newly developed GREEN primer for the plastering professional. It is green in colour but more importantly the product is environmentally friendly as it contains around 20% of recycled material.

PLASPRIME® can be used on virtually any surface to provide the perfect preparation to which skim plaster is to be applied.

### Form Supplied: Viscous Liquid

**Pack Sizes:** 10L

**Colour range:** Green

**Contains:** Blend of polymers, additives and 20% recycled material

### Properties

PLASPRIME® is particularly useful when re-skimming old walls. In such circumstances the walls can be of various materials and surface finish such as old paint or wallpaper paste residues. Further, it is often the case that part of a wall may be porous and others completely sealed. Using PLASPRIME® helps with these problems and gives uniform drying, making finishing much quicker and easier.

### Usage/Preparation

The surface should be clean and sound; prepare any loose or flaking material mechanically to remove. Existing paint should be checked for soundness and adhesion. Do not apply directly on to wallpaper. It is assumed that the surface is sufficiently strong to support the weight of any applied plaster. Take care on artex to ensure plaster is applied in two passes, the first being scraped on to ensure good contact. See limitations for glossy surfaces.

### General

Apply PLASPRIME® with a soft brush to give an even texture over the entire surface and allow to thoroughly dry. The drying time is dependant on the surface porosity and environmental conditions.

Once the primer has dried apply skim plaster in the normal manner. PLASPRIME® can be used over most building materials such as brick, block, concrete, plaster, render, well adhered paint and adhesive residues and plasterboard.

### Coverage

The coverage of PLASPRIME® is dependant on the surface smoothness and absorbency. As a guide 1 litre of PLASPRIME® will cover approximately 3 – 4 square metres.

### Cleaning

Clean all tools and splashes in water before the product dries.

### Limitations

For internal use only and not suitable for priming prior to adhesive fixing of plasterboards. For glossy surfaces, external use, bonding renders and very high absorbency backgrounds use Sovereign Plasprime X.

### Health and Safety

Not Classified.

This product should be stored, handled and used in accordance with good hygiene practices and in conformity with any legal regulations.

**Storage:** Between 5°C - 30°C.

**Shelf Life:** At least 12 months unopened.

Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that product, techniques and codes of practice are under constant review and changes occur without notice; please ensure you have the latest updated information.

# SOVEREIGN

Sovereign Chemicals Limited  
Park Road, Barrow in Furness,  
Cumbria.  
Tel: 01229 870800  
Fax: 01229 870850  
Technical Support Line: 0845 603 0722  
Web: [www.sovchem.co.uk](http://www.sovchem.co.uk)  
Email: [sales@sovchem.co.uk](mailto:sales@sovchem.co.uk)