


Point Master, 15kg



DESCRIPTION:

Stonefix Point Master is a single component joint filling system for the simple and rapid pointing of paved areas with joints over 5mm. Ready for use and easily applied by brushing into joints. A unique blend of cross-linked polymers and high quality aggregates that bind together chemically on exposure to the atmosphere. Once cured, Point Master forms a hard wearing joint that is unaffected by weather.

FEATURES:

- Natural Stone / Paving
- Fast Application
- External Use
- Polymer Modified
- Eco-friendly – No VOCs
- Easy to Use



CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk

PLEASE NOTE

Point Master cures by reaction with oxygen and usually cures within 8-24 hours at typically temperatures (15 – 20°C). Rainfall during or immediately after application will weaken the product, protection is essential.

Efflorescence is an inherent characteristic of concrete paving, particularly in riven and reconstituted stone, and is not promoted by the use of Point Master.

After periods of heavy rain fall deposits of dirt and pollution may be highlighted on the Point Master joints. This is easily removed by brushing when dry or low pressure washer.

To ensure a long lasting finish of Paving & joints we would recommend sealing with Stonefix Paving Sealer after application of Point Master.

APPLICATION

Preparation

All joints to be pointed should be dry, free from weeds, dirt or debris. Joints to be pointed using Point Master must have a Minimum width of 5mm throughout the full depth of the joint. The depth of the joint should not be less than 25mm. Point Master should not be applied in rain or wet conditions. If rain threatens after application, Point Master must be protected until cure has taken place. Point Master should not be applied at sub zero temperatures.

Mixing

Point Master is supplied ready to use, however some compaction of the product may occur in storage and light raking of the product may be required.

Placement

Open the Point Master pack and empty sufficient product to treat approximately 10 sqm of paving. Using a soft broom, work the Point Master into the joints making sure that each joint is completely filled and compacted.

A pointing tool may be used to compacted further and achieve a traditional finish.

COLOURS

Available in Buff and Grey.

COVERAGE

Approximate coverage per 15Kg pack: Subject to compaction.

Joint width	Paving Dimension (with a joint depth of 25mm)		
	50mm x 250mm	450mm x 450mm	600mm x 600mm
5mm	9.75m ²	16.5m ²	20.0m ²
6mm	8.25m ²	14.25m ²	16.5m ²
7mm	6.75m ²	12.5m ²	13.0m ²
8mm	6.0m ²	11.0m ²	12.5m ²
9mm	4.75m ²	9.0m ²	11.0m ²
10mm	4.5m ²	8.25m ²	9.75m ²

STORAGE CONDITIONS

Store in cool, dry conditions in original sealed container. Once the foil bags is punctured or opened, the contents will harden.

SHELF LIFE

12 months when stored according to manufactures instructions.

CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk

PACKAGING

Buff available in 15kg tubs (2 x 7.5kg bags per tub).

Grey available in 12kg tubs (2 x 6kg bags per tub).

HEALTH & SAFETY INSTRUCTIONS

- Product presents a low hazard in correct use.
- Keep out of reach of children.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.
- If swallowed, seek medical advice immediately and show this container or label.

For further information, please request the material safety data sheet for this product.

QUALITY CONTROL

All STONEFIX products are factory blended, tested and packaged to quality control procedure in accordance with BS EN ISO 9001 series.

INFORMATION, PRICES AND ORDERING

Please call + 44 (0)1845 576514.

CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK

T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk