



## DECLARATION OF PERFORMANCE

### EC CONSTRUCTION PRODUCTS REGULATION EN 12326 ROOFING AND CLADDING SLATE

<b>DOP Number</b>		<b>08/2022</b>			
1. Unique Identification Code of the Product Type		<b>Stoneleaf Classic</b>			
2. Type or batch allowing identification of the construction product		400x250, 500x250, 500x300			
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer.		Slate for discontinuous Roofing and Cladding			
4. Name, registered name, or trademark and contact address of the manufacturer		Stoneleaf Building Materials, Templewood Industrial Estate, Stock Road, West Hanningfield, Chelmsford, CM2 8LA			
5. Where applicable, name and contact address of the authorised representative.		N/A			
6. System or systems of assessment and verification of constancy of performance		AVCP System 4			
<b>7. Declared Performance</b>					
<b>Essential Characteristics for Pitched Roof Coverings</b>	<b>Performance</b>				<b>Harmonised Technical Specification</b>
Mechanical Resistance	Average MOR:				
	Transverse	<b>63.5 Mpa</b>	Longitudinal	<b>78.9 Mpa</b>	
	Characteristic MOR:				
	Transverse	<b>52.8 Mpa</b>	Longitudinal	<b>68.1 Mpa</b>	
External Fire Performance					Deemed to satisfy
Reaction to Fire					Deemed to satisfy Class A1
<b>Dimensional Tolerances</b>					
Slate Type	Very Smooth	Smooth	Normal	Textured	
Deviation from Flatness		< 1.0%			
Nominal Thickness & Variation		+/- 35%			
Deviation from Declared Length					<± 5mm
Deviation from Declared Width					<± 5mm
Deviation from squareness					<± 1mm
Deviation from straightness of edges					<± 5mm or 1%
<b>Durability</b>					
Water Absorption					W1/A1 (0.37%)
Freeze Thaw					Not required
Thermal Cycle Test					T1
Carbonate Content					0.6%
SO <sub>2</sub> Exposure Test ≤ 20%					S1
Non Carbonate Content					0.6%
Release of Dangerous Substances					None in conditions of use as roofing or external cladding

EN 12326-2: 2012

The product(s) identified in Points 1 and 2 are in conformity with the declared performance in Point 7. This declaration of performance is the sole responsibility of the manufacturer identified in Point 4.

Authorised by:

**Robert M Curry, Managing Director, Stoneleaf Building Materials Ltd**



Stoneleaf Building Materials, Templewood Industrial Estate, Stock Road, West Hanningfield, Chelmsford, CM2 8LA  
Tel: 01277 841 555, Fax: 01277 841 666, Email: sales@stoneleafslates.co.uk, www.stoneleafslates.co.uk