



Boxed Glazed Roof Access Hatch

Generated on 03.01.2018

Detailed description

Thermally broken, multi-pane glazed roof access hatch with glazed, manually operated hinged door and horizontal lid with one opening section.

Available with mill finish aluminium, or polyester powder-coated internally/externally in two colours to any standard RAL colour.

Product guidance - As Standard

Material:

Aluminium cover and frame.

Glazing:

35.5 mm-thick, sealed, double-glazed unit, which includes 6 mm-thick, toughened, K-polished all-round outer pane, 20 mm-thick, argon-filled warm edge silver spacer bar and 9.5 mm-thick toughened and laminated inner pane. 1.5 W/m²K U-value.

Product specification

Manufacturer

- Name: Surespan Ltd
- Web: www.surespancovers.com
- Email: sales@surespancovers.com
- Tel: +44 (0)1922 711185
- Fax: +44 (0)1922 497943
- Address: Leamore Close, Leamore Enterprise Park, Walsall, West Midlands WS2 7NL

Product reference SRHG-BOX

Size []

Colour/ Finish

- Internal Mill - Standard.
Polyester powder-coated - Insert RAL colour requirement.
- External Mill - Standard.
Polyester powder-coated - Insert RAL colour requirement.

Upstand Four-sided glazed upstand

Surespan Ltd



Surespan Ltd

Leamore Close

Leamore Enterprise Park

Walsall

West Midlands

WS2 7NL

Tel: +44 (0)1922 711185

www.surespancovers.com
sales@surespancovers.com



Solid aluminium upstand

Insulation	50 mm-thick standard insulation - 0.43 W/m ² K. 50 mm-thick non-combustible mineral wool insulation - 0.63 W/m ² K.
Operation	24 V electric motors Gas springs - Standard.
Locking	None L01 Cablock - Standard. L02 Cablock with hasp and staple L04 Cablock with external padlocking handle L06 ABS Euro cylinder with external key locking and thumb-turn options L07 European deadlock with internal and external key operation