



SRHG GLAZED ROOF HATCH

Material:	Aluminium.
Glazing:	The 35.5mm sealed double glazed unit will comprise Pilkington 6mm toughened K polished all round outer pane, 20mm Warm Edge silver spacer Bar argon filled, Pilkington 9.5mm toughened & laminated inner pane. This sealed glazed unit has a U-Value of 1.5 W/m ² K.
Insulation:	The remaining part of the hatch is filled with CFC and HCFC free insulation. This combination offers a high level of thermal insulation, together with excellent sound absorption properties. Fire rating to 1 hour as an additional option.
Frame Height:	313mm in height as standard. The upstand has a purpose made flashing to accept the roof felt (supplied by others and fitted under manufacturers instructions) flush to exterior insulation.
Insulation:	GWP (Global Warming Potential) of 3. ODP (Ozone Depletion Potential) of 0.
Locking:	The lid is held shut by a heavy duty stainless steel cab lock and in the interest of safety as standard, can only be opened from the inside unless otherwise specified. Other locking options are available on request.
Lifting:	Complete with gas spring assisted opening to ensure the minimum of effort to open the double skinned aluminium lid. Electrically operated are available options.
Finish:	The cover comes self colour as standard or can be provided polyester powder coated to any standard stocker RAL colour as an additional option.
Note:	We recommend all hatches are installed on a 5° pitch to stop water ponding.

