



## SRHG Glazed Roof Hatch

Generated on 08.01.2018

### Detailed description

Thermally Broken single leaf glazed roof hatches are manufactured in aluminium with an optional internal or external polyester powder coated finish.

The gas spring assisted opening lid is supported by heavy-duty stainless steel hinges and fixings.

35.5 mm sealed double glazed unit will comprise Pilkington 6 mm toughened K polished all round outer pane, 20 mm Warm Edge silver spacer Bar argon filled, Pilkington 9.5 mm toughened and laminated inner pane.

### Product guidance - As Standard

#### Insulation:

50 mm HCFC and CFC free polyisocyanurate - U-value of 0.43 W/m<sup>2</sup>K.

#### Glazing

35.5 mm Double Glazed unit with Pilkington 6 mm toughened K polished all round outer pane, 20 mm Warm Edge silver spacer Bar argon filled, Pilkington 9.5 mm toughened and laminated inner pane

### Product specification

#### Manufacturer

- Name: Surespan Ltd
- Web: [www.surespancovers.com](http://www.surespancovers.com)
- Email: [sales@surespancovers.com](mailto:sales@surespancovers.com)
- Tel: +44 (0)1922 711185
- Fax: +44 (0)1922 497943
- Address: Leamore Close, Leamore Enterprise Park, Walsall, West Midlands WS2 7NL

<b>Product reference</b>	SRHG
<b>Size</b>	600 x 600 mm 750 x 750 mm 900 x 750 mm 900 x 900 mm 1000 x 1000 mm 750 x 1500 mm 1200 x 1200 mm

Surespan Ltd



**Surespan Ltd**  
Leamore Close  
Leamore Enterprise Park  
Walsall  
West Midlands  
WS2 7NL

Tel: +44 (0)1922 711185

[www.surespancovers.com](http://www.surespancovers.com)  
[sales@surespancovers.com](mailto:sales@surespancovers.com)



<b>Material</b>	Aluminium - Mill finish as standard. Stainless steel
<b>Upstand</b>	200 mm thermally broken and insulated 300 mm thermally broken and insulated - As.standard. 385 mm thermally broken and insulated - Superior insulation only.
<b>Colour/ Finish</b>	
- Internal	Not required Polyester powder coating - Any RAL colour, insert requirements.
- External	Not required Polyester powder coating - Any RAL colour, insert requirements.
<b>Operation</b>	24 V electric motors Concealed electric motors Fixed glazed skylight Gas springs
<b>Locking options</b>	L01 Cablock - As.standard. L02 Cablock with hasp and staple L04 Cablock with external padlocking handle
<b>Accessories</b>	[None] [Extended skirt liner] - Used in conjunction with retractable ZIP ladder. [Fixed external handhold] [Retractable ZIP ladder] [SureGuard hand railing]