

ROOFLIGHTS Fixed Circular SUREDOME

Fixed Circular Rooflight Overview

With the Circular skylights, we have produced a distinctive product of unrivalled design, the smooth edging of the glazing which requires no screwed connections only acts to reinforce this statement.

STANDARD FEATURES

- Triple Polycarbonate Layers
- High thermal insulation to 1.8 W/m²K
- 150mm GRP Upstand
- Wide variety of standard sizes
- Decibel Rating of 22 dB

Description:

Flat Roof Circular Skylight with a 150mm GRP Upstand.

Glazed:

30mm sealed double glazed units comprise of a 6mm toughened outer pane with a 16mm argon filled cavity and two 4mm laminated inner panes.

Finish:

Surespan offer Clear and Opal diffused layer variants while the upstand comes in white as standard.

Upstand:

Surespan 150mm GRP upstands are thermally insulated to U-value 0.8 W/m²K with water drip edge, ensuring that no rain water can run over the edge and into the building.

Options:

Sold with a variety of accessories including shade protectors, burglary protection and ManSafe Latches

Fixing:

Specially developed security fixings ensure a slimline finish as opposed to top mounted external

Note:

Upstands can be provided and delivered separately to the SUREDOMES, enabling upstand installation during early stages of development. This can prevent accidental damage to the Rooflights.

LAYERS

Also Available:

Double Layer



U-Value
1.1 W/m²K

Triple Layer




U-Value
0.7 W/m²K

Quad Layer



Special Designs:

ThermoPlan



U-Value
0.83 W/m²K

Heatstop



Reflects infrared
Heat

