

PROVEN PERFORMANCE

COG ROAD, BARRY

TOPFLOW
SCREED C BELITEX

Product Topflow Screed C Belitex
Main contractor South Wales Screeding Ltd
Location Barry, South Wales
Date of completion 01/2016

Tarmac was approached to advise on a potential flooring solution for a project where there were challenging issues and short timescales involved.

THE CHALLENGE

The client was looking for a floor screed product which could be laid at a thinner depth and, due to time constraints, be laid quickly and easily. It also needed to be quick drying, able to take foot traffic as soon as possible and with a high quality finish.

OUR SOLUTION

Tarmac proposed Topflow Screed C Belitex, a cement based, free flowing screed.

Topflow Screed C Belitex dries within 14 - 21 days versus a minimum of 40 - 75 days with other traditional or flowing screed products and it can take foot traffic after just 24-48 hours.

Up to 120m² can be laid in 45 minutes versus a whole day with traditional screed and it can also be laid in thinner depths than traditional screed.

This product is stronger than traditional screed, with no reinforcement or manual compaction required and produces an excellent SR2 smooth level surface finish.

RESULTS AND BENEFITS

Tarmac supplied 14m³ of Topflow Screed C Belitex which covered an area of 280sq metres. The contractor had the product placed and finished within 1 and a half hours and their customer was able to traffic the floor within 48 hours.

By using this product the client was able to save time and progress other aspects of the build sooner. This meant that the overall project could be completed more quickly.

For more details contact topflowscreed@tarmac.com or call **0800 1 218 218**

TARMAC.COM/TOPFLOWSCREED

©2015 Tarmac Trading Limited.

0000/0015