

FLUTE





LEDs covered by satin tube to reduce glare and diffuse light



Aluminium reflector version

LED version with polycarbonate refractor

INTEGRAL PENDANTS FOR LEDs AND TC-T COMPACT FLUORESCENT LAMPS



SPECIFICATION

- Refractor in polycarbonate and reflector in anodised aluminium
- Gloss silver finish extruded aluminium body
- Satin tube over LEDs reduces glare and diffuses light
- Opal acrylic visor for TC-T refractor version only
- Lamp versions use flexible tri-lamp ballast
- Fitted with 2m black cable
- Fitted with 4000K LEDs

LED CHARACTERISTICS

Ra 80+	°K 4000	L70/B10 60K	LL/CW 53.8
P/U P	% >85	R/Rx R	

For LED characteristics explanation see www.thorlux.com/led-characteristics

RANGE

LAMP	CAT. No.	HEIGHT (mm)	DIAMETER (mm)	APPROX. kg
Polycarbonate Refractor				
24W LED	SH 15156L	365	312	2.0
36W LED	SH 15157L	365	312	2.0
26/32/42W TC-T	SH 12969J	350	312	1.0
Aluminium Reflector				
24W LED	SH 15158L	365	312	2.0
36W LED	SH 15159L	365	312	2.0
26/32/42W TC-T	SH 12970J	350	312	1.0

CIRCUIT TYPE - J - non-dimming (HF fluorescent) / L - non-dimming (LED)

TC-T Versions - lamps must be ordered separately

ACCESSORIES

DESCRIPTION	CAT. No.	APPROX. kg
Opal acrylic visor assembly ▲	VZ 11120	0.04

▲ Suitable for use with SH12969J version only

Web link: [Lamps](#)