

# Tortread™ SP Floor Systems

## System data sheet



Providing Practical Solutions



### Where can it be used

#### Buildings

Tortread™ SP Floor Systems is suitable for use in locations where light duty floor coatings are required such as:

- Warehouses
- Factories
- Workshops
- Garages
- Showrooms

### The Tor service available to you

- Unrivalled expertise and knowledge
- Nationwide team of area managers and technical personnel
- Free site survey of your floor
- Free comprehensive specification writing service
- On site technical back-up for live projects

### Product Appearance

Range includes: Semi gloss or smooth, plain colour floor coatings. Anti slip floor coatings.

### What does it do?

Tortread™ SP Floor Systems are a range of single-pack, general use, light duty floor coatings that offer an easy to apply, cost effective, surface with good wear resistance.

### System Features:

- Single-pack systems
- Easy to use
- Quick drying formulae
- Good resistance to abrasion
- Excellent resistance to oil and grease
- Easy to maintain
- Anti slip versions available
- Attractive finishes available in a range of colours

### What does the system include?

<b>1st Coat</b>	Tortread™ SP Stabilising Sealer (AK602)
<b>2nd &amp; 3rd Coat</b>	The system finish is chosen from: Tortread™ SP Anti-Slip Paint System (AK723) Tortread™ SP Floor Paint System (AK724)

## Technical information

	Tortread™ SP Stabilising Sealer	Tortread™ SP Anti-Slip	Tortread™ SP Floor Paint
<b>Typical Coverage</b>	6m <sup>2</sup> per litre	7m <sup>2</sup> per litre	8m <sup>2</sup> per litre
<b>Application</b>	Brush/ roller	Brush/short pile roller	Short pile roller
<b>Pack size</b>	5 litres	5 litres	5 litres
<b>Touch dry</b>	2 hours	2 hours	2 hours
<b>Hard dry</b>	6-8 hours	Within 16 hours	Within 16 hours
<b>Minimum overcoating time</b>	16 hours	8 hours	8 hours
<b>Maximum overcoating interval</b>	48 hours	7 days	7 days

Coverage rates may vary depending on surface profile and application conditions etc. Drying/curing times will vary depending on ambient/surface temperatures.

## How to specify

The following specification for semi-gloss finish onto bare concrete is included for demonstrative purposes only.

**Always consult a representative of Tor Coatings prior to specifying or applying.**

By brush or roller, apply one full coat of Tortread™ SP Stabilising Sealer (AK602) at a coverage rate of 6 square metres per litre. Allow to dry. Overcoating time minimum 16 hours, maximum 48 hours.

By brush or short pile roller, apply two full coats of Tortread™ Floor Paint (AK724) at a coverage rate of 8 square metres per litre per coat. Allow to dry. Overcoating time minimum 8 hours, maximum 7 days.

Tor Coatings offer a free site survey service, and all of our Area Business Managers are fully trained and able to carry out full site assessments. A detailed and bespoke specification will then be issued.

Call Tor Coatings on **0191 410 6611** to arrange your site survey.



Easy to maintain

## Technical support

Tor Coatings national team of Area Business Managers is supported by a dedicated customer service team, a large team of paint chemists and a dedicated technical help desk.

Call **0191 411 3148** for assistance from our helpdesk, or visit **[www.tor-coatings.com](http://www.tor-coatings.com)** to find out more.



Providing Practical Solutions

Tor Coatings Limited, Portobello Industrial Estate,  
Birtley, County Durham, DH3 2RE.

**Tel:** +44 (0)191 410 6611 **Fax:** +44 (0)191 492 0125

**E-mail:** [enquiries@tor-coatings.com](mailto:enquiries@tor-coatings.com)

**Web:** [www.tor-coatings.com](http://www.tor-coatings.com)