

# ABNER 3



ABNER is a circular downlight designed with a deep seated light source and efficient lens system for reduced glare. The uniquely designed housing and integrated heat management offers a clean and elegant styling combined with robustness and precision. The design of the reflector/lens combination enables various beam patterns ranging from narrow to wide beam.


ABNER3 has excellent colour rendering properties, constant colour quality throughout the service life and high energy efficacy making it the perfect solution for all retail and commercial lighting applications.

ABNER3 is available in various dimming options - Triac, 1-10V, DALI and non-dimmable.

Please order drivers separately.



Technical Specification			
System Power Consumption	8W	10W	12W
LED Power Consumption	5.8W	8.5W	10.2W
CRI	Ra80 + Standard Ra90 Optional		
Luminaire Luminous Flux @ CRI80	560lm (27K) 600lm (30K) 640lm (40K) 640lm (50K)	870lm (27K) 950lm (30K) 1000lm (40K) 1000lm (50K)	950lm (27K) 1050lm (30K) 1100lm (40K) 1100lm (50K)
Driver	Remote		
Adjustability	Fixed		
Housing	Die-Cast Aluminium		
Trim Finish	White		
Reflector	Polycarbonate Electroplated		
Weight	0.26kg		
IP Rating	IP20 IP65 with Clear or Frosted Glass		
Lamp life L70	50,000 hours		
Operating Ambient Temp.	-10°C to +40°C		



## Colours Available

Cool White - 5000K
Neutral White - 4000K
Warm White - 2700K, 3000K

## Optics Available

15°, 24°, 36° - Lens + Reflector
45°, 60° - Reflector

## Product Code

TRY - ABNER3 - 8W - 27K - 15 - IP20
10W 30K 24 IP65C
12W 40K 36 IP65F
50K 45
60

Note: Please choose appropriate driver from Tryka range.

## Product Code Example:

TRY-ABNER3-12W-30K-24-IP20

As part of our continuous product development we reserve the right to amend these specifications without prior notice.

Tryka L.E.D. Ltd., Unit 3 Station Works, Station Road, Shepreth, Nr. Royston, Herts, U.K SG8 6PZ. Tel: +44 (0) 1763 260666 www.tryka.com