

MINISPOT 30



MINISPOT30 is a circular spotlight designed with a smaller aperture for low glare architectural lighting applications.

The fixture is uniquely designed with built-in light engine and ultra narrow aperture. Excellent colour rendering properties, constant colour quality throughout the service life and high energy efficacy make it a perfect solution for accent lighting applications and displays.

Available with a wide range of colour temperatures, beam angles and dimming options to suit your requirements.

Please order drivers separately.



Colours Available


Cool White - 5000K
Neutral White - 4000K
Warm White - 2700K, 3000K

Optics Available

15°, 24°, 36°

Technical Specification

System Power Consumption	1W	2W	3W
CRI	Ra80+ Standard Ra95 Optional		
Luminaire Luminous Flux	70lm	135lm	190lm
Driver	Remote		
Adjustability	Fixed		
Housing	Aluminium		
Baffle Finish	Black		
Trim Finish	Aluminium, White		
Weight	0.05kg		
Dimensions	30mm Dia x 46mm H		
Cutout opening	27mm Dia		
IP Rating	IP20		
Lamp life L70	50,000 hours		
Operating Ambient Temp.	-10°C to +40°C		



Product Code

TRY - MINISPOT30 - 1W - 27K - 15- IP20
2W 30K 24
3W 40K 36
50K

Note: Please choose appropriate driver from Tryka range.

Product Code Example:

TRY-MINISPOT30-2W-30K-24-IP20

As part of our continuous product development we reserve the right to amend these specifications without prior notice.

Tryka L.E.D. Ltd., Unit 3 Station Works, Station Road, Shepreth, Nr. Royston, Herts, U.K SG8 6PZ. Tel: +44 (0) 1763 260666 www.tryka.com

