

**General data**

Panel	1 strip	1820 x 190 mm
Total thickness		12,5 mm
Numbers of panels per pack		6
m <sup>2</sup> per pack		2,0750 m <sup>2</sup>

**Panel build up**

Toplayer	PEFC controlled sources	2,5 mm
Core board		HDF Mastercore
Backing layer	PEFC controlled sources	1,35 mm
Tongue and groove	Length Width	Spruce or Pine Uniclic Perfect fold 3.0

**Surface layer**

Wood species	Oak
Origine	Europe
Finishing	Matt lacquer
Grading	Marquant

**Installation**

Floating	On Pergo underlay	CF installation instructions
Glued to subfloor	Pergo MS polymere resin	CF installation instructions

**Warranty**

Domestic use	Conditions in each pack	25 years
Uniclic connection		Lifetime
Commercial		On request

**Finishing**

UV curing varnish		5 - 7 layers	
Wear resistance	SIS 923509 DIN 68861	Falling sand S 33	800 - 1000 100 - 1050
Scratch resistance		Anti-scratch top coat	
Stain resistance	EN 13442	All except blue ink Blue ink	class 5 class 3
CE	EN 14342: 2008-09		DOP PCO 0501
Castor chairs		Use soft castors, type W (EN 12529) and/or suitable office mat	
Slip resistance	CEN/TS 15676		USRV 50-52
Emission of formaldehyde	EN 717-1		E1
PCP			below detection limit
Heat resistance	EN 12664		0,121 m <sup>2</sup> /KW
Underfloor heating	Suitable	CF special installation instructions	
Reaction to fire	EN 14342	CWFT	Cl-s1

**Ecological certificates**

U-zeichen	Z.156.606-898
AFFSET	A+
Nordic ecolabel	3029-0001
PEFC	PEFC/07-32-37
M1	OK
EPD	On request



EN14342:2013

Wood Floor - Multi layer Parquet EN 13489

